

ASHLAND CHEMICAL COMPANY -- TECTYL 802 A;LUBRICATING OIL -- 9150-00-271-8427

=====  
Product Identification  
=====

Product ID:TECTYL 802 A;LUBRICATING OIL

MSDS Date:01/28/1987

FSC:9150

NIIN:00-271-8427

MSDS Number: BDRWZ

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL COMPANY

Address:INDUSTRIAL CHEMICALS & SOLVENTS

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Info Phone Num:614-

790-3333

Emergency Phone Num:606-324-1133

CAGE:5A188

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH

ZIP:43017

Country:US

Phone:614-889-4505

CAGE:5A188

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HEAVY NAPHTHENIC DISTILLATE

C

AS:64742-52-5  
RTECS #:PY8035000  
Fraction by Wt: 85-100%  
OSHA PEL:5MG/CUM,AS OIL MIST  
ACGIH TLV:5MG/CUM,AS OIL MIST

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF  
EYES,REDNESS,TEARING.MAY CAUSE SLIGHT IRRITATION OF SKIN;IRRITATION  
OF NASAL AND RESPIRATORY PASSAGES;INGESTION MAY CAUSE G.I. TRACT  
IRRITATION,NA  
USEA,VOMITING & DIARRHEA. CHRONIC: NO DATA  
AVAILABLE;POSSIBLE DERMATITIS.  
Effects of Overexposure:SEE HEALTH HAZARDS DATA.  
Medical Cond Aggravated by Exposure:NOT KNOWN:POSSIBLE SKIN PROBLEM.

=====  
===== First Aid Measures =====

First Aid:EYES:WASH WITH PLENTY OF WATER FOR 15 MINUTES,CALL A  
PHYSICIAN. SKIN:WASH THOROUGHLY WITH SOAP & WATER;DO NOT USE  
CONTAMINATED/CLOTHES. INHALATION:REMOVE TO FRESH AIR;GET MEDICAL  
ATTENTION AT ONCE. IN GESTION:GE  
T MEDICAL ATTENTION AT ONCE.NEVER  
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point:>200F/94C  
Extinguishing Media:FOAM,CO\*2,OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED  
AREA.  
Unusual Fire/Explosion Hazard:NEVER USE WELDING/CUTTING TORCH ON OR  
NEAR DRUM;PRODUCT CAN IGNITE EXPLOSIVELY.

=====  
===== Accidental Release Measures =====

Spill Rel

ease Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE  
INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL DRY AND WELL VENTILATED  
AREA.KEEP AWAY FROM HEAT,OPEN FLAMES AND SPARKS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL  
MIST/VAPOR IF ABOVE TLV/PEL.

Ventilation:LOC

AL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:FULL PROTECTIVE CLOTHES.EYE-WASH OR SAFETY  
SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE  
VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:V6

Boiling Pt:B.P. Text:302F/150C

Vapor Pres:1.0 MMHG

Vapor Density:>1.0

Spec Gravity:0.928-0.945

Eva

poration Rate & Reference: