

OCTAGON PROCESS INC. -- VV-L-800 C,AM 1 (OCTOIL 90-2),3012301 -- 9150-00-273-2389

=====
Product Identification
=====

Product ID:VV-L-800 C,AM 1 (OCTOIL 90-2),3012301

MSDS Date:06/28/1993

FSC:9150

NIIN:00-273-2389

MSDS Number: BDRZW

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Info Phone Num:201-945-9400/313-1187

Em

ergency Phone Num:201-945-9400/800-424-9300(CHEMTREC)

Preparer's Name:J. J. BURGARD

CAGE:82925

=== Contractor Identification ===

Company Name:AMEREX CORPORATION

Address:7595 GADSDEN HWY E

Box:81

City:TRUSSVILLE

State:AL

ZIP:35173-0081

Country:US

Phone:205-655-3271

CAGE:54905

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

Company Name:DRESSER ARGUS INC

Address:36 BRIDGE ST

Box:

City: BROOKLYN
State: NY
ZIP: 11201-1115
Country: US
Phone: 718-643-1540
CAGE: 84583
Company Name: OCTAGON PROCESS INC.
Address: 596 RIVER ROAD
Box: City: EDGEWATER
State: NJ
ZIP: 07020
Country: US
Phone: 201-945-9400
CAGE: 82925

=====
Composition/Information on Ingredients
=====

Ingred Name: NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 100%
Other REC Limits: NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation: NO Skin: NO Ingestion:
NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE AND CHRONIC- MAY CAUSE MILD EYE
IRRITATION AND REDNESS. PROLONGED OR REPEATED SKIN CONTACT MAY
CAUSE MILD IRRITATION. NO ADVERSE EFFECTS EXPECTED FROM INHALATION.
PRACTICALLY NON-TOXIC BY INGESTION. MAY CAUSE SLIGHT IRRITATION TO
GASTROINTESTINAL TRACT.
Explanation of Carcinogenicity: DATA PER MSDS
Effects of Overexposure: EYE, SKIN AND GASTROINTESTINAL TRACT IRRITATION
Medical Cond Aggr
Affected by Exposure: NOT KNOWN

=====
First Aid Measures
=====

First Aid: CALL A DOCTOR IF SYMPTOMS PERSIST. EYE: IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP &
WATER. INHALED: NON NORMALLY REQUIRED. ORAL: IF CONSCIOUS, DRINK
WATER AND INDUCE VOMITING. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method: COC
Flash Point: 320F, 160C
Lower Limits: 1.0
Upper Li

mits:7.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT & REIGNITE

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL. DO NOT ALLOW MATERIAL

TO ENTER DRAINS, SEWERS OR WATERWAYS. RECOVER FREE LIQUID IF POSSIBLE. ABSORB REMAINING PRODUCT WITH INERT MATERIAL AND PLACE INTO PROPER CONTAINERS FOR DISPOSAL. COMPLY WITH HAZPOWER (29 CFR 1910.120).

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM HEAT, FLAME & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:WASH

HANDS WITH SOAP AND WATER BEFORE EATING, DRINKING OR USING TOILET FACILITIES. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. DO NOT GENERATE MISTS OR VAPORS. CLEAN CONTAMINATED EQUIPMENT BEFORE STARTING ANY REPAIR WORK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKING IN A CONFINED AREA OR MISTING IS OCCURRING, USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING

RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPOR

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:RUBBER OR NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONT

AMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

USE FORCED VENTILATION TO MINIMIZE VAPOR CONCENTRATION. AVOID BREATHING
VAPORS OR MISTS. ALL USERS SHOULD CONSULT MSDS BEFORE HANDLING THIS
MATERIAL. DISPOSE OF OIL SOAKED FOOTWARE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:550F,288C

Vapor Pres:< 0.01

Spec Gravity:0.89

Evaporation Rate & Reference: