View NSN Online: https://aerobasegroup.com/nsn/9150-00-273-8663

WELCH VACUUM TECHNOLOGY (FORMERLY SARGENT-WELCH CO -- WELCH DUOSEAL HIGH VACUUM PUMP OIL #1407K -- 9150-00-273-8663

============= Product Identification =================

Product ID:WELCH DUOSEAL HIGH VACUUM PUMP OIL #1407K

MSDS Date:08/29/1991

FSC:9150

NIIN:00-273-8663

MSDS Number: BDSBP === Responsible Party ===

Company Name: WELCH VACUUM TECHNOLOGY (FORMERLY SARGENT-WELCH CO

Address:7300 N LINDER AVE

Box:1026 City :SKOKIE

State:IL ZIP:60077-3217

Country:US

Info Phone Num:312-267-5300

Emergency Phone Num:312-267-5300

CAGE:IO538

=== Contractor Identification ===

Company Name: SARGENT-WELCH SCIENTIFIC CO

Address:7300 N LINDER AVE

Box:1026 City:SKOKIE State:IL ZIP:60076

Country:US

Phone:312-267-5300

CAGE:64484

Company Name: WELCH VACUUM TECHNOLOGY INC/THOMAS INDUSTRIES INC

Address:7300 NORTH LINDER AVE

Box:183 City:SKOKIE State:IL

ZIP:60076-0183 Country:US

Phone: 708-676-8800 EXT. 1

CAGE:IO538

====== Co

mposition/Information on Ingredients ========

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY

PARAFFINIC CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: REFINED HEAVY PARAFFINIC DISTILLATES

CAS:64741-88-4

Fraction by Wt: SEE #1%

Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

========== Hazards Identification ================

LD50 LC50 Mixture:LD50 (ORAL RAT)=15G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. AVOID BREATHING OF MIST. PROLONGED OVEREXPOSURE MAY RESULT IN DERMATITIS AND RESPIRATORY DIFFICULTIES. ANIMAL STUDIES ALSO SHOW AN EFFECT ON THE KIDNEYS FOR EXPOSURE TO MATERIAL S SIMILAR TO THIS. AT HIGH TEMPERATURES, MISTS ABOVE TLV MAY CAUSE LUNG DAMAGE.

**Explanation of Car** 


cinogenicity: NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES AND SKIN UPON CONTACT.
IRRITATION OF THE RESPIRATORY TRACT, HEADACHES, DIZZINESS,
ANESTHETIC EFFECT AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS
INCLUDING DEATH IN RARE CASES. INGESTION MAY CAUSE CRAMPS AND
DIARRHEA. INHALATION MAY CAUSE BRONCHITIS OR PULMONARY IRRITATION.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF EYE,

SKIN

AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS IRREGULAR OR HAS STOPPED, START RESU SCITATION AND ADMINISTER OXYGEN. GET MEDICAL HELP IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION AT



Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLIN

## **G AND BEFORE**

EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

USE AIR-SUPPLIED RESPIRATORY EQUIPMENT IF EXPOSED TO HOT FUMES. TREAT EMPTY CONTAINERS AS DANGEROUS; DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE CONTAINERS TO HEAT, FLAME, SPAR KS, PILOT LIGHTS, STATIC ELECTRICITY. RESIDUE MAY BE DIFFICULT TO REMOVE.

======== Physical/Chemical Properties ==========

HCC:V6 NRC/State Lic Num:N ONE Boiling Pt:B.P. Text:750F,399C Vapor Pres:1 AIR=1 Spec Gravity:0.88

Evaporation Rate & Deference: