

MICHEL AND PELTON CO -- 140 FLASH NAPTHA -- 6850-00-274-5421

=====
Product Identification
=====

Product ID:140 FLASH NAPTHA

MSDS Date:01/01/1985

FSC:6850

NIIN:00-274-5421

MSDS Number: BDSFV

=== Responsible Party ===

Company Name:MICHEL AND PELTON CO

Address:5743 LANDREGAN ST

City:EMERYVILLE

State:CA

ZIP:94608-2515

Country:US

Emergency Phone Num:901-527-9520

CAGE:91341

=== Contractor Identificatio

n ===

Company Name:MICHEL AND PELTON CO

Address:5743 LANDREGAN ST

Box:City:EMERYVILLE

State:CA

ZIP:94608-2515

Country:US

CAGE:91341

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROCARBONS,SATURATED; TLV PER MFG.

Fraction by Wt: 94.6%

ACGIH TLV:200 PPM

Ingred Name:HYDROCARBONS,AROMATIC;TLV PER MFG

Fraction by Wt: 5.4%

ACGIH TLV:200 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALE:IRRITNT,DROWSY,COLLA

PSE, TWITCH, COMA, &
LATER PNEUMONIA, EYE/SKIN: IRRITANT; INGEST: HARMFUL

=====
First Aid Measures
=====

First Aid: INHALE: REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED; EYES/SKIN: FLUSH W LG AMTS H*2O FOR 15 MIN; INGEST: RINSE MOUTH,
GET IMMEDIATE MEDICAL ATTENTION (DO NOT INDUCE VOMIT; DRINKING OF
VEGETABLE OIL, IE OLIVE OIL, IS INDICATED IN LITERATURE.

=====
Fire Fighting Measures
=====

Flash Point: 143F, 61.7C TCC

Extinguishing Media: CO*2, DRY CHEM, FOAM, WATER SPRAY (DOT P 5800.2)

Fire Fighting Procedures: SELF-CONTAINED BREATHING APP; H*2O SPRAY COOL CONT.

Unusual Fire/Explosion Hazard: CONTAINERS MAY EXPLODE IN HEAT OF FIRE

=====
Accidental Release Measures
=====

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIMINATE IGNITION
SOURCES. PROVIDE VENTILATION. STOP LEAK. H*2O SPRAY COOL CONT, IF
HOT; ABSORB W COMMERCIAL ABSORBENT, PLACE IN COVERED CONTAINERS.

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW
FIRE RISK AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM
PHYSICAL DAMAGE.

Other Precautions: MAINTAIN STRICT HYGIENE, AVOID PHYSICAL CONTACT,
REMOVE & WASH CONTAMINATED CLOTHING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: FOR EXPOSURE: SELF-CONTAINED BREATHING APP/APPR RESPIRATOR
Ventilation: MECHANICAL (GENERAL/LOCAL EXHAUST)

Protective Gloves: IMPERMEABLE

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: FULL WORK CLOTHING.

Supplemental Safety and Health

II TYPE; BOILING POINT RANGE: 360-410; PROLONGED CONTACT WITH SKIN MAY
CAUSE DERMATITIS.

=====
Physical/Chemical Properties
=====

HCC: V4

Boiling Pt: B.P. Text: 385F, 196C

Vapor Pressure: 2.3

Vapor Density: 5.5

Specific Gravity: 0.7728

Evaporation Rate & Reference: 3

Solubility in Water: NEGLIGIBLE

Appearance and Odor: TRANSPARENT LIQUID; H

YDROCARBON SOLVENT ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:IGNITION SOURCES

Hazardous Decomposition Products:EXPECT CO FROM INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.

HANDLE AND DISPOSE IN FULL COMPLIANCE WIT ALL APPLICABLE

INTERNATIONAL,FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.