View NSN Online: https://aerobasegroup.com/nsn/9150-00-281-2060

AMERICAN OIL & SUPPLY CO -- PQ R P-172 -- 9150-00-281-2060

Product ID:PQ R P-172 MSDS Date:01/01/1985 FSC:9150 NIIN:00-281-2060 MSDS Number: BDSRQ === Responsible Party === Company Name: AMERICAN OIL & SUPPLY CO Emergency Phone Num:201-589-0250 CAGE:DO810 === Contractor Identification === Company Name: AMERICAN OIL & SUPPLY CO Address:233 WILSON AVE **City:NEWARK** St ate:NJ ZIP:07105 Country:US Phone:201-589-0250 CAGE:DO810 Company Name: AMERICAN OIL AND SUPPLY CO Address:239 WILSON AVE City:NEWARK State:NJ ZIP:07105-3824 Country:US Phone:201-589-0250 CAGE:92895

Ingred Name:LUBRICATING OIL Fraction by Wt: 100%

Effects of Overexposure: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION

First Aid:INGEST:DO NOT INDUCE VOMITING.CALL PHYSICIAN.SKIN:WASH THOROUGHLY W/SOAP & WARM WATER.EYES:FLUSH WITH WATER FOR 15 MIN OR UNTIL IRRITATION SUBSIDES

Flash Point:285F (COC) Lower Limits:1 Upper Limits:6 Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG OR SPRAY Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS

Unusual Fire/Explosion Hazard: AVOID BREATHING FUMES

Spill Release Procedures:RECOVER FREE LIQUID.ADD ADSORBENT(SAND,EARTH,SAWDUST ETC)TO SPILL AREA.KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATERCOURSES BY DIKING OR IMPOUNDING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED/MAY ENTER, SEWERS,WATERCOURSES,EXTENSIVE LAND AREA

Handling and Storage Prec

autions:DO NOT HANDLE OR STORE NEAR

HEAT, SPARKS, FLAME OR STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE

Other Precautions: AVOID BREATHING OIL MIST.REMOVE OIL-SOAKED CLOTHING & LAUNDER BEFORE RE-USE.DISCARD OIL-SOAKED SHOES.WASH SKIN THOROUGHLY WITH SOAP & WATER AFTER HANDLING

Respiratory Protection:SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED/ENCLOSED SPACES Ventilation:LOCAL EXHAUST TO CAPTURE FUMES & VAPORS Protective Gloves:CHEM RESISTANT Eye Protection:SPLASH GOGGLES/FACE SHLD Other Protective Equipment:CHEMICAL RESISTANT APRON Supplemental Safety and Health

HCC:V6 Boiling Pt:B.P. Text:500F Vapor Density:9 Spec Gravity:0.884 Evaporation Rate & amp; Reference: