View NSN Online: https://aerobasegroup.com/nsn/8010-00-281-2076

CORONADO PAINT COMPANY INC -- 69-27 SUP PENETRATING OIL WOOD STAIN

MSDS Safety Information

FSC: 8010

NIIN: 00-281-2076 MSDS Date: 05/23/1991 MSDS Num: BDSRW

Product ID: 69-27 SUP PENETRATING OIL WOOD STAIN

MFN: 01

Responsible Party Cage: 33200

Name: CORONADO PAINT COMPANY INC

Address: 308 OLD COUNTY RD

Citv:

EDGEWATER FL 32132

Info Phone Number: (904) 428-6461

Emergency Phone Number: (904) 428-6461

Proprietary Ind: Y Review Ind: Y Published: Y

Preparer Co. when other than Responsible Party Co.

Cage: 33200

Name: CORONADO PAINT COMPANY, INC.

Address: 308 OLD COUNTY ROAD City: EDGEWATER FL 32132-1812

Contractor Summary

Cage: 33200

Name: CORONADO PAINT COMPANY, INC.

Address: 308 OLD COUNTY ROAD City: EDGEWATER FL 32132-1812

Phone: 904-428-6461

Item Description Information

Item Manager: GSA Item Name: STAIN

Specification Number: TT-S-711C

Unit of Issue: GL UI Container Qty: 4

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: EYES: SEVERE IRRITATION, REDNESS, TEARING, & DURRED VISION. INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS, HEADACHE,

NTOXICATION W/EUPHORIA, UNCONSCIOUSNESS, IRRITATION TO THE MUCOUS MEMB RANES, NOSE & THROAT IRRITATION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA.

Explanation Of Carcinogenicity: NONE

Signs And Symptions Of Overexposure: INGESTION: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE PNEUMONITUS WHICH CAN BE FATAL. INHALATION:

REPEATED/PROLONGED OVEREXPOUSRE TO SOLVENTS CAUSES PERMANENT BRAIN & amp; NERVOUS SYSTEM DAMAGE.

First Aid: EYES/SKIN: FLUSH W/LUKE

WARM WATER FOR 15 MINS. INHALATION: REMOVE

TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 TO 8 OUNCES OF LIQUIDS. NE VER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Handling and Disposal

Spill Release Procedures: ABSORB LIQ

UID ON PAPER, VERMICULITE, FLOOR ABSORBANT,

OR OTHER ABSORBANT MATERIAL. PREVENT RUNOFF TO SEWERS STREAMS OR OTHER BODIES

OF WATER. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREAD ING, PUMP LIQUID TO SALVAGE TANK.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & DESTROY BY INCINERATION.

Handling And Storage Precautions: AVOID CONTACT W/EYES & DESCRIPTION OF STREET AND STREET AND STREET AVOID BREATHIN

G OF

VAPORS.

Other Precautions: WASH W/SOAP & DEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. KEEP WELDING OR CUTTING EQUIPMENT AWAY FROM PRODUCT.

Fire and Explosion Hazard Information

Flash Point Text: 105F Lower Limits: 1% Upper Limits: 6%

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPAR

ATUS W/A FULL

FACEPLATE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN

FIGHTING FIRES.

Unusual Fire/Explosion Hazard: VAPORS MAY BE >AIR & MAY TRAVEL ALONG THE GROUND BEFORE IGNITION & FLASH BACK TO IGNITION SOURCE.

Control Measures

Respiratory Protection: IF TLV OR ANY COMPONENT EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS AD

VISED IN ABSENSE OR PROPER

ENVIRONMENTAL CONTROL. ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLIMEN TED TO REUDCE EXPOSURE.

Ventilation: AS REQUIRED

Protective Gloves: RESISTANT, NATURAL RUBBER, NEOPRENE

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHING, EYE BATH, SAFETY SHOWR, APRON

& BOOTS.

Supplemental Safety and Health: 6.9 LBS/GAL. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & Samp; INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=====

Physical/Chemical Properties

B.P. Text: 390F Vapor Pres: 0.10 Vapor Density: >AIR Spec Gravity: N/K1

Evaporation Rate & Deference: SLOWER THAN BU AC

Percent Volatiles by Volume: 81.33%

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HEAT, FLAME, ELE

CTRICAL EQUIPMENT, SPARKS, & OPEN FLAME. Materials To Avoid: STRONG OXIDIZING AGENTS Hazardous Decomposition Products: CO2, CO, VARIOUS HYDROCARBONS Hazardous Polymerization Indicator: NO ______ **Toxicological Information** ______ **Ecological Information** ______ _____ MSDS Transport Information ______ _____ Regulatory Information _____ _____ Other Information ______ HAZCOM Label ______ Pr oduct ID: 69-27 SUP PENETRATING OIL WOOD STAIN Cage: 33200 Company Name: CORONADO PAINT COMPANY, INC. Street: 308 OLD COUNTY ROAD City: EDGEWATER FL

City: EDGEWATER FL Zipcode: 32132-1812

Health Emergency Phone: (904) 428-6461

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998 Origination Code: G

Hazard And Precautions: EYES: SEVERE IRRITATION, REDNESS, TEARING, & Description of the second secon

BLURRED VISION. INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS,

HEADACHE, INTOXICATION W/EUP

HORIA, UNCONSCIOUSNESS, IRRITATION TO THE MUCOUS MEMB RANES, NOSE & MEMB RANES & MEMB R

Disclaimer (provided with this information by the compiling agenci es): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instructio

n who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.