

CORONADO PAINT COMPANY INC -- 69-27 SUP PENETRATING OIL WOOD STAIN

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-281-2076  
MSDS Date: 05/23/1991  
MSDS Num: BDSRW  
Product ID: 69-27 SUP PENETRATING OIL WOOD STAIN  
MFN: 01  
Responsible Party  
Cage: 33200  
Name: CORONADO PAINT COMPANY INC  
Address: 308 OLD COUNTY RD  
City:  
EDGEWATER FL 32132  
Info Phone Number: (904) 428-6461  
Emergency Phone Number: (904) 428-6461  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 33200  
Name: CORONADO PAINT COMPANY, INC.  
Address: 308 OLD COUNTY ROAD  
City: EDGEWATER FL 32132-1812

=====  
Contractor Summary  
=====

Cage: 33200  
Name: CORONADO PAINT COMPANY, INC.  
Address: 308 OLD COUNTY ROAD  
City: EDGEWATER FL 32132-1812  
Phone: 904-428-6461

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: STAIN  
Specification Number: TT-S-711C  
Unit of Issue: GL  
UI Container Qty: 4

=====  
Ingredients  
=====

=====  
Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYES: SEVERE IRRITATION, REDNESS, TEARING, & BLURRED VISION. INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS, HEADACHE,

INTOXICATION W/EUPHORIA, UNCONSCIOUSNESS, IRRITATION TO THE MUCOUS MEMBRANES, NOSE & THROAT IRRITATION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: INGESTION: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS CAUSES PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

First Aid: EYES/SKIN: FLUSH W/WATER

WARM WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 TO 8 OUNCES OF LIQUIDS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Handling and Disposal  
=====

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBANT, OR OTHER ABSORBANT MATERIAL. PREVENT RUNOFF TO SEWERS STREAMS OR OTHER BODIES OF WATER. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DESTROY BY INCINERATION.

Handling And Storage Precautions: AVOID CONTACT W/EYES & SKIN. CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. AVOID BREATHING

G OF  
VAPORS.

Other Precautions: WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING, OR  
USING TOILET FACILITIES. KEEP WELDING OR CUTTING EQUIPMENT AWAY FROM PRODUCT.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text: 105F

Lower Limits: 1%

Upper Limits: 6%

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPAR

ATUS W/A FULL

FACEPLATE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN  
FIGHTING FIRES.

Unusual Fire/Explosion Hazard: VAPORS MAY BE >AIR & MAY TRAVEL ALONG THE  
GROUND BEFORE IGNITION & FLASH BACK TO IGNITION SOURCE.

=====  
Control Measures  
=====

Respiratory Protection: IF TLV OR ANY COMPONENT EXCEEDED, A NIOSH/MSHA JOINTLY  
APPROVED AIR SUPPLIED RESPIRATOR IS AD

VISED IN ABSENSE OR PROPER

ENVIRONMENTAL CONTROL. ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE  
IMPLIMENTED TO REDUCE EXPOSURE.

Ventilation: AS REQUIRED

Protective Gloves: RESISTANT, NATURAL RUBBER, NEOPRENE

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHING, EYE BATH, SAFETY SHOWR, APRON  
& BOOTS.

Supplemental Safety and Health: 6.9 LBS/GAL. INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=====  
Physical/Chemical Properties  
=====

B.P. Text: 390F

Vapor Pres: 0.10

Vapor Density: >AIR

Spec Gravity: N/K1

Evaporation Rate & Reference: SLOWER THAN BU AC

Percent Volatiles by Volume: 81.33%

=====  
Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT, FLAME, ELE

CTRICAL EQUIPMENT, SPARKS, & OPEN  
FLAME.

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: CO2, CO, VARIOUS HYDROCARBONS

Hazardous Polymerization Indicator: NO

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
HAZCOM Label  
=====

Pr  
Product ID: 69-27 SUP PENETRATING OIL WOOD STAIN  
Cage: 33200  
Company Name: CORONADO PAINT COMPANY, INC.  
Street: 308 OLD COUNTY ROAD  
City: EDGEWATER FL  
Zipcode: 32132-1812  
Health Emergency Phone: (904) 428-6461  
Label Required IND: Y  
Date Of Label Review: 12/16/1998  
Status Code: C  
Label Date: 12/16/1998  
Origination Code: G  
Hazard And Precautions: EYES: SEVERE IRRITATION, REDNESS, TEARING, &  
BLURRED VISION. INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS,  
HEADACHE, INTOXICATION W/EUP

HORIA, UNCONSCIOUSNESS, IRRITATION TO THE MUCOUS  
MEMBRANES, NOSE & THROAT IRRITATION. INGESTION: GASTROINTESTINAL  
IRRITATION, NAUSEA, VOMITING, & DIARRHEA. INGESTION:  
ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE PNEUMONITIS WHICH CAN BE  
FATAL. INHALATION: REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS CAUSES  
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====

Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction

who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.