

SEAGRAVE COATING CORP CHEMRAY DIV -- F117B ACID COMP-PT-B -- 8030-00-281-2726

=====
Product Identification
=====

Product ID:F117B ACID COMP-PT-B

MSDS Date:01/01/1985

FSC:8030

NIIN:00-281-2726

MSDS Number: BDSTQ

=== Responsible Party ===

Company Name:SEAGRAVE COATING CORP CHEMRAY DIV

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phon

e Num:201-245-1111

CAGE:8D124

=== Contractor Identification ===

Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:8D124

=====
Composition/Information on Ingredients
=====

Ingred Name:PHOSPHORIC ACID (SARA III)

CAS:7664-38-2

RTECS #:TB6300000

Fraction by Wt: 16.0%

OSHA PEL:1 MG/M3/3 STEL

ACGIH TLV:1 MG/M3/3 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:IS

OPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 65.0%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 19.0%

===== Hazards Identification =====

Effects of Overexposure:MAY BE IRRITATING TO SKIN, EYES, AND
RESPIRATORY SYSTEM

===== First Aid Measures =====

First Aid:WASH EXPOSED AREA FREELY W/WATER. IF OVEREXPOSURE, REM
OVE
SUBJECT TO WELL-VENTILATED AREA. CALL PHYSICIAN IF NECESSARY. IN
CASE OF CONTACT W/EYES, FLUSH W/WATER AND CONTACT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:53F FED STD 141
Lower Limits:1.4
Upper Limits:12.0
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE
Fire Fighting Procedures:ALCOHOL FOAM IS INEFFECTIVE,MAY BE USED WHEN
OTHER UNAVAILAB

===== Accidental Release Measures =====

Spill
Release Procedures:FOLLOW GENERAL CLEANING PROCEDURES. SMALL
SPILLS MAY BE WASHED AWAY W/WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM
OPEN FLAMES AND PHYSICAL ABUSE.
Other Precautions:THE MATERIAL IS SHIPPED AS 4 GAL OF RESIN COMPONENT &
1 GAL OF ACID CATALYST IN A 5 GAL PAIL. THE 2 COMPONENTS SHOULD BE
MIXED AND ALLOWED 30 MIN. INDUCTION. SECURE ALL SOURCES OF
IGNITION.

=====

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS AND EYE PROTECTION

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL)

Protective Gloves:YES

Eye Protection:YES

Supplemental Safety and Health

CONFORMS TO MIL-P-15328C

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:165F

Vapor Pres:33

Vapor Density:2.55

Spec Gravity:0.92

Evaporation Rate & Reference:1.0 BUTYL ACETATE

Sol

ubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:OPEN FLAMES AND UNGROUNDED EQUIPMENT

=====
Disposal Considerations
=====

Waste Disposal Methods:RETURN UNUSED MATERIALS TO SUITABLE CONTAINS.

Disclaimer (provided with this information by the compiling agencies):

This informat

ion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.