

KOPPER'S CO.,INC. -- P-605-66 WASH PRIMER, PT A -- 8030-00-281-2726

=====
Product Identification
=====

Product ID:P-605-66 WASH PRIMER, PT A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-281-2726

MSDS Number: BDSTT

=== Responsible Party ===

Company Name:KOPPER'S CO.,INC.

Address:3000 KOPPERS BLDG

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:LO123

=== Contractor Identification ===

Company Name:

KOPPER'S CO.,INC.

Address:3000 KOPPERS BLDG

Box:City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:LO123

Company Name:KOPPERS CO INC

Address:3000 KOPPERS BLDG

Box:City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:80592

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ALCOHOL

Fraction by Wt: 19.3%

ACGIH TLV:S,C,50 PPM

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 53%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV

:400 PPM/500STEL;9192

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
Fraction by Wt: 8.6%
OSHA PEL:0.1 MG/M3 (CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:COPPER PHTHALO CYANINE BLUE
Fraction by Wt: 1.0%
ACGIH TLV:0.1MG/CUM,MFR

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 6.0%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Effects of Overexposure:HEADACHE, NAUSEA. EY
ES/SKIN:MODERATELY
IRRITATING.

=====
First Aid Measures
=====

First Aid:REMOVE VICTIMS FROM VAPORS, RESTORE BREATHING IF
NECESSARY.SKIN:WASH W/SOAP & WATER. EYES:FLUSH W/WATER 15 MINS.
CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:63F,17C TOC
Lower Limits:1.4
Extinguishing Media:CO*2,FOAM OR DRY CHEMICAL
Fire Fighting Procedures:DO NOT USE WATER.
Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIV
E MIXTURE BETWEEN
UPPER & LOWER EXPLOSIVE LIMITS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. APPLY SAWDUST OR
OTHER ABSORBENT MATERIAL. KEEP MATERIAL FROM SPREADING. PUT IN
METAL CNTAINER & SEAL FOR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:FLAMMABLE; STORE AWAY FROM OPEN FLAME
& HIGH HEAT. DO NOT TAKE INTERNALLY. AVOID PROLONGED C

ONTACT W/SKIN

& EYES. AVOID BREATHING VAPORS.

Other Precautions:PHYSICAL DATA:BP:82-118C. VAP PRESS:4.0(N-BUTYL ALCOHOL)TO 33.0(ISOPROPYL ALCOHOL).ALSO CONTAINS 8.5% VINYL RESIN & 3.6% WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP FOR EXPOSURE OF CONCERN.

Ventilation:ADEQUATE TO KEEP LOWER LEVEL BELOW LEL.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:RUBBER SOLES MUST BE

WORN(NO STATIC

ELECTRICITY).

Supplemental Safety and Health

CONFORMS TO MIL-P-15328C. PT A OF A 2 PART KIT. PT B IS T-152-66 ACID

COMPONENT, ALSO TO BE USED W/T-120-66 WASH PRIMER THINNER.

CONTAINER SIZE;0.8 FAL PER PKG.KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F6

Boiling Pt:B.P. Text:180-244F

Vapor Density:>1.0

Evaporation Rate & Reference: