

TECH SPRAY,INC -- TT-B-846,BUTYL ALCOHOL:NORMAL(BUTANOL) -- 6810-00-281-6928

=====  
Product Identification  
=====

Product ID:TT-B-846,BUTYL ALCOHOL:NORMAL(BUTANOL)

MSDS Date:01/01/1985

FSC:6810

NIIN:00-281-6928

MSDS Number: BDTBM

=== Responsible Party ===

Company Name:TECH SPRAY,INC

Address:88 HUGHES STREET

Box:949

City:AMARILLO

State:TX

ZIP:79105

Country:US

Info Phone Num:800-692-4677 OR 800-858-4

043

Emergency Phone Num:806-372-8523

CAGE:JO768

=== Contractor Identification ===

Company Name:TECH SPRAY INC

Address:1001 NW 1ST

Box:949

City:AMARILLO

State:TX

ZIP:79105-0949

Country:US

Phone:806-372-8523

CAGE:54700

Company Name:TECH SPRAY,INC

Address:88 HUGHES STREET

Box:949

City:AMARILLO

State:TX

ZIP:79105

Country:US

Phone:800-692-4677 OR 800-858-4043

CAGE:JO768

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BUTYL ALCOHOL(N-BUTANOL)(CAS #71-36-3)

RTECS #:OE

1400000  
Fraction by Wt: 100%  
ACGIH TLV:(C) 50 PPM

===== Hazards Identification =====

Effects of Overexposure:IRRITANT TO EYES &  
SKIN,ANESTHETIC,CONJUNCTIVITIS,DERMATITIS,RESPIRATORY  
INFLAMMATION,HEADACHE

===== First Aid Measures =====

First Aid:FLUSH EYES THOROUGHLY WITH WATER.WASH OUT CONTAMINATED SKIN  
WITH SOAP & WATER.APPLY OPHTHALMIC CORTISONE FOR CONJUNCTIVITIS &  
KERATITIS.STOMACH WASH,IF SWALLOWED,F  
OLLOWED BY SALINE CATHARIS.

===== Fire Fighting Measures =====

Flash Point:105F TOC  
Extinguishing Media:WATER,DRY CHEMICAL,CARBON DIOXIDE,FOAM MAY BE  
INEFFECTIVE  
Fire Fighting Procedures:WATER SPRAY MAY HELP TO KEEP CONTAINERS  
COOL,TO DIFFUSE GAS.  
Unusual Fire/Explosion Hazard:SOURCES OF IGNITION,REACTS WITH  
EXPLOSIVES,OXIDIZING MATERIALS,ORGANIC PEROXIDES,POISONS,& ISOTOPES

===== Accidental Release Measures =====

Spil  
I Release Procedures:REMOVE LEAKING PACKAGES TO SAFE AREA,AWAY FROM  
FIRE OR FLAME,AVOID BREATHING CONCENTRATED VAPORS

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,UNLIGHTED PLACE AWAY  
FROM SOURCES OF IGNITION & FROM EXPLOSIVES,OXIDIZING  
MATERIALS,ORGANIC PEROXIDES,POISONS & RADIOACTIVE MAERIALS.  
Other Precautions:DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F.DO  
NOT DROP CONTAINERS.WEAR SAFETY GLASSES,SELF C

CONTAINED BREATHING

APPARATUS & RUBBER PROTECTIVE CLOTHING.AVOID PROLONGED OR BREATHING OF GASES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS

Ventilation:AS REQUIRED TO CONTROL THE TLV IN AIR

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:RUBBER PROTECTIVE CLOTHING

Supplemental Safety and Health

FED SPEC TT-B-846 HAS BEEN CANCELLED EFFECTIVE AUT 21,1979;STORAGE CODE F3

IS ASSIGNED ON THE BASIS OF THAT FLASH PT IS LOWER THAN 100F.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:244F

Spec Gravity:0.8109

Evaporation Rate & Reference:N.A.

Appearance and Odor:CLORLESS LIQUID,FUSEL OIL OR WINE LIKE ODOR

Percent Volatiles by Volume:7.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING/CORROSIVE MATL.

Stability Condition to Avoid:SOURCE OF I

GN.

Hazardous Decomposition Products:CO,CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CANS.SPRAY MAERIAL INTO A FURNACE UNDER CONTROLLED PROCEDURES.INCINERATION WILL BECOME EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner wha

tsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.