View NSN Online: https://aerobasegroup.com/nsn/6810-00-281-6928

MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION -- BUTYL ALCOHOL, NORMAL 6810-00-281-6928

Product ID:BUTYL ALCOHOL,NORMAL MSDS Date:01/01/1987 FSC:6810 NIIN:00-281-6928 MSDS Number: BDTBP === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Address: PARIS BYPASS Box:M City:PARIS State:KY ZIP:40361 Country:US Info Phone Num:314-982-5000 Emergency Phone Num:314-982-5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US

Phone:908-859-2151 CAGE:62910

Ingred Name:N-BUTYL ALCOHOL (SARA III) CAS:71-36-3 RTECS #:EO1400000 Fraction by Wt: >99% OSHA PEL:100 PPM ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

=================

Effects of Overexposure:INH:MAY IRRIT,NOSE/THROAT;ING:MAY CAUSE NAUSEA,DIARRHEA,VOMIT;SKIN:DEMATITIS;EYES:IRRIT,BLURRD VISN.

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGEST:IF SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE VOMIT.NOTHING BY MOUTH IF UNCON;SKIN/EYE EXPOSURE:RMV CONTMNTD CLOTHG.WASH SKIN W/SOAP & H*20 .FLUSH SKIN/EYES W/ LG H*20:GET MED HELPIMMEDIATLY

Flash Point:29C(84F)-C.C
Lower Limits:1.4
Upper Limits:11.3
Extinguishing Media:WATER,DRY CHEM,FOAM,CO*2;WATER SPRAY:TO KEEP EXPSD CANS COOL
Fire Fighting Procedures:USE H*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG.
Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIMITS; AUTO IGN TEMP:

========== Accidental Release Mea

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RESP PROTCTION & PROTCTV CLOTHG.KEEP OUT OF SURF H*20,SEWRS/CONFND AREAS;SM SPILL:ABSORB W/PAPER TOWELS.EVAP UNDER FUME HOOD THEN BURN CAREFULLY;LG SPILL:DIKE AREA.CONTAI N & RECOVER SPILL IF POSS;SHOVL RESDUE INTO DRUMS.

Handling and Storage Precautions: KEEP IN TIGHTLY CLOSED CONTAINERS AT COOL, DRY, VENTILATED PLACE. PROTECT
AGAINST PHYSICAL DAMAGE.
Other Precautions: AVOID BREATHING DUST. USE W/ADEQUATE VENTILATION.
KEEP CONTAINERS CLOSED. WASH THOROUGHLY AFTER HANDLING. AVOID SKIN, EYES & CLOTHING CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SUPPLIED AIR RESPIR/SCBA; ESCAPE: GAS MASK Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION Supplemental Safety and Health MSDS FROM MFR DATED:JAN 1985 CONFORMS TO OSHA HAZ COMM STD.

HCC:F3 Boiling Pt:=117.8C, 244.F Vapor Pres:5 Vapor Density:2.6 Spec Gravity:0.8 Evaporation Rate & amp; Reference:0.46(BU-ACETATE=1) Solubility in Water:SLIGHT Appearance and Odor:CLEAR,COLORLESS LIQUID.ODOR LIKE FUEL OIL BUT WEAK

Stabilit y Indicator/Materials to Avoid:YES OXIDIZERS;ALUMINUM,CHROMIUM TRIOXIDE. Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CO,CO*2 WHEN HEATED TO DECOMPOSITION

Waste Disposal Methods:COLLECT SPILLS & ATOMIZE IN A RCRA-APPROVED COMBUSTION CHAMBER EQUIPPED W/AFTER-BURNER & SCRUBBER SYSTEM,OR ABSORB IN VERMICULITE,DRY SAND,OR OTHER SIMILAR MATL FOR DISPOSAL AS HAZARD WASTE IN AN APPR OVED RCRA FACILITY I/A/W LOCAL,STATE & FED REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suita bility of this information to their particular situation.