View NSN Online: https://aerobasegroup.com/nsn/9160-00-285-2044

Product ID:TYPE I GRADE A TECHNICAL PARAFFIN

MSDS Date:01/01/1987

FSC:9160

NIIN:00-285-2044

MSDS Number: BDTLW === Responsible Party ===

Company Name: KINDT-COLLINS CO. Emergency Phone Num: 216 - 252-4122

CAGE:EO495

=== Contractor Identification ===
Company Name:KINDT COLLINS CO

Address:126

51 ELMWOOD AVENUE Box:City:CLEVELAND

State:OH

ZIP:44111-5911 Country:US

Phone:216-252-4122/CHEMTREC 800-424-9300

CAGE:33629

Company Name: KINDT-COLLINS COMPANY

Address:12651 ELMWOOD AVENUE

City:CLEVELAND

State:OH ZIP:44111

Phone: (216) 252-4122

CAGE:EO495

======= Composition/Information on Ingredients ========

Ingred Name: HYDROCARBON WAX

ACGIH TLV:2MG/CUM(FUME)

=========== Hazards Identification ==============

Effects of Overexposure: SLIGHTLY IRRITATING TO EYES;

CAUSE MILD RESPIRATORY IRRITATION.
======================================
First Aid:USE STANDARD FIRST AID PROCEDURE.IF HOT WAX STRIKES THE SKIN,IMMERSE THE AREA IN WATER.IF AVAILABLE,APPLY ICED WATER OR COLD PCKS(DO NOT DO IT IF BURNED AREA IS >14% OF THE BODY).DONOT TRY TO REMOVE W AX FROM A BURN AFTER IT HAS COOLED,SEEKMGD ATTN
======================================
Flash Point:>400F/204C(COC) Extinguishing Media:CO*2, FOAM, DRY CHEM & H*20 FOG. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR. Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:SM MOLTEN SPILL:ALLOW WAX TO COOL & REMOVE AS A SOLID. LG MOLTEN SPILL:WEAR RESPIRATOR & PROTECTIVE CLOTHING.SHUT OFF SOURCE OF LEAK IF SAFETY TO DO SO.DIKE AND CONTAIN.ALLOW WAX TO COOL AND REMOVE AS A SOLID.
======= Handling and Storage =============
Handling and Storage Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF EXCED TLV,NIOSH/MSHA APPR SELF-CNTND BRTHG APP (POS PR MODE) Ventilation:NORMAL Protective Gloves:YES Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:PROTECTIVE CLOTHING Supplemental Safety and Health MSDS DATED 11-1-85
========= Physical/Chemical Properties ==========
HC

MOLTEN WAX FUME MAY

Boiling Pt:B.P. Text:>600F/315C Vapor Pres:0.1 Spec Gravity:0.86 Solubility in Water:NEGLIBLE Appearance and Odor:SLIGHT ODOR,WATER IN COLOR
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:CO,CO*2, & UNIDENTIFIED ORGANIC COMPOUNDS
====== Disposal Considerations ==========

Waste Disposal Methods:PLACE IN AN APPROPRIATE DISPOS AL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

C:N1

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suita bility of this information to their particular situation.