

AMERON PROTECTIVE COATINGS -- GREY 16187 -- 8010-00-286-7731

=====  
Product Identification  
=====

Product ID:GREY 16187

MSDS Date:01/01/1987

FSC:8010

NIIN:00-286-7731

MSDS Number: BDTWV

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=

== Contractor Identification ==

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 44.1%

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

ACGIH TLV:300 PPM

=====  
Hazards Identification  
=====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF  
RESPIRATORY TRACT & NERVOUS SYSTEM DEPRESSION. SKIN/EYES:  
IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION

===== First Aid Measures =====

First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.  
OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:85F  
Lower Limits:1.1  
Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR  
FIREMEN.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHIN  
G VAPORS. REMOVE W/INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE FALL OF LIQUID TO EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIO

SH APPROVED PAINT RESPIRATOR/AIR SUPPLIED  
RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION &  
CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by V

olume:60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE AND FEDERAL  
REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of  
the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.