

JOTUN-BALTIMORE COPPER PAINT CO. -- FORMULA 104,MIL-P-15146,DULL BLACK PAINT --
8010-00-286-7854

=====
Product Identification
=====

Product ID:FORMULA 104,MIL-P-15146,DULL BLACK PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7854

MSDS Number: BDTYH

=== Responsible Party ===

Company Name:JOTUN-BALTIMORE COPPER PAINT CO.

Emergency Phone Num:(301) 539-0045

CAGE:85319

=== Contractor Identification =

==
Company Name:JOTUN-BALTIMORE COPPER PAINT CO.

CAGE:85319

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40.2%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:EYE,SKIN,RESPIR TRACT IRRIT. RPTD/PRLNG SKIN
CNTCT: POSS DERMATITIS.

=====
First Aid Measures
=====

First Aid

:FUMES-MOVE PERSON TO WELL VENT AREA. RESTORE BREATHING.GET
MED ATTN. SKIN CNTCT-WIPE W/CLEAN CLOTH. WASH THOROUGHLY W/ SOAP &
WATER.EYE CONTCT-FLUSH THOROUGHLY W/WATER.GET MED ATTN.

=====
Fire Fighting Measures
=====

Flash Point:102F (TOC)

Lower Limits:1.1

Upper Limits:6.0

Extinguishing Media:CO*2,DRY CHEMICAL OR FOAM

Fire Fighting Procedures:SEE SUPP DATA

Unusual Fire/Explosion Hazard:KEEP AWAY FROM IGNIT SOURCES.CLSD CONTNR
MAY EXPLODE IF EXPOSE

D TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. BURN SWEEPINGS IN SAFE AREA.

===== Handling and Storage =====

Handling and Storage Precautions: STORE BELOW 100F. KEEP CONTAINERS CLOSED & AWAY FROM HEAT & OPEN FLAME

Other Precautions: DO NOT APPLY TO HOT SURFACES. EFFECT OF OVEREXPOSURE: POSS HEADACHE, DIZZINESS & EVENTUAL UNCONSCIOUSNESS OR COMA. AVOID Prolonged Contact w/skin & Vapor/Spray Mist Inh. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SPRAY APPLICATION (OPEN & CLOSED AREAS): USE NIOSH/MSHA APPROVED EQUIP.

Ventilation: MFR RECOMM LOCAL EXHAUST. DILUTION VENTILATION FOR MECHANICAL.

Protective Gloves: SOLVENT RESIST

Eye Protection: SPLASH PROOF GOGGLES

Supplemental Safety and Health

SPEC FIRE FIGHT PROC: H₂O INEFFECT ON FIRE

-CAN USE TO COOL CLOSED CONTAINER

EXPOSED TO EXTREME HEAT/FIRE TO PREVENT PRESSURE BUILD UP & POSS AUTO IGNITION OR EXPLOSION. CONTAINER SIZE : 1 GAL.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 300-400 F

Vapor Density: 3.9

Spec Gravity: 1.11

Evaporation Rate & Reference: