

DEVOE MARINE COATINGS CO -- FORMULA 20,DOD-E-699,EXTERIOR GRAY DECK --  
8010-00-286-9083

===== Product Identification =====

Product ID:FORMULA 20,DOD-E-699,EXTERIOR GRAY DECK

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-9083

MSDS Number: BDTZH

=== Responsible Party ===

Company Name:DEVOE MARINE COATINGS CO

Address:4000 DUPONT CIRCLE

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

CAGE:EO141

=== Co

ntractor Identification ===

Company Name:DEVOE MARINE COATING CO.

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:EO141

Company Name:GROW GROUP INC DEVOE AND REYNOLDS CO DIV

Address:4000 DUPONT CIRCLE

Box:City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-361-2536

CAGE:97758

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE755500

0

Fraction by Wt: 45%

OSHA PEL:100 PPM

Ingrid Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 100F/37C (PMCC)

Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM

Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL  
CONTAINERS

Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILD-UP CLOSED  
CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCE  
S OF IGNITION.AVOID BREATHING

VAPORS,VENT AREA.CONTAIN SPILLED MATERIAL & REMOVE WITH INERT  
ABSORBENT AND NON-SPARKING TOOLS.STORE IN CLOSED CONTAINERS UNTIL  
PROPERLY DISPOSED OF.

===== Handling and Storage =====

Handling and Storage Precautions:DONOT STORE ABOVE 120F/48C OR NEAR  
FIRE OR OPEN FLAME.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO  
COMPLY WITH OSHA 1910.106

Other Precautions:CLOSE CONTAINERS AFTER USE.DO NOT REUSE EMPTY  
C  
ONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST WITH EXPLOSION PROOF  
MOTOR

Protective Gloves:SOLVENT RESIST

Eye Protection:SOLVNT RESIST EYE WEAR

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

MFR CODE: FORMULA 20,MD-7745,MIL-P-699

===== Physical/Chemical Properties =

=====

HCC:F4

Boiling Pt:B.P. Text:150F/65C

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:48

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS,RUBBER SOFTENS

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE,OXIDES  
OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACC

ORDANCE WITH LOCAL,STATE AND

FEDERAL REGULATIONS.INCINERATE ONLY IN APPROVED FACILITY.DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek com

petent professional advice to verify and

assume responsibility for the suitability of this information to their  
particular situation.