

AMERON PROTECTIVE COATINGS -- BLACK SHIPBOTTON -- 8010-00-290-4247

=====
Product Identification
=====

Product ID:BLACK SHIPBOTTON

MSDS Date:01/01/1985

FSC:8010

NIIN:00-290-4247

MSDS Number: BDVFJ

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *98-2*

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 7.0%

Other REC Limits:100 PPM

OSHA PEL:100 PPM

ACGIH TLV:100 PPM, SKIN

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000

LBS

Ingred Name:HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE
98-2

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 11.0%

Other REC Limits:50 PPM

OSHA PEL:410 MG/CUM

ACGIH TLV:205 MG/CUM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE
Effects of Overexposure:ANESTHETIC,
IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A
PHYSICIAN IF CONDITIONS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:60F
Lower Limits:1.0
Extinguishing Media:SMALLFIRES-CARBON DIOX
IDE OR DRY CHEM. LARGE
FIRES-FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS

=====
===== Handling and Storage =====

Handling and Storage Precautio

ns:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH PAINT RESPIRATOR OR AIR SUPPLIED
RESPIRATOR
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY
Supplemental Safety and Health
RESPIRATO
R USE BASED ON CHEM. CONC. AND CONDITIONS OF USE

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:237-287F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:56.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====
=

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek comp

etent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.