

PRATT AND LAMBERT INC -- 741-610 -- 8010-00-297-0556

===== Product Identification =====

Product ID:741-610

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0556

MSDS Number: BDVYN

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

Emergency Phone Num:316-733-1361

CAGE:92216

=== Contractor Identification ===

Company Name:PRAT

T AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 35.0%

OSHA PEL:100 PPM

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.24%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:AROMATIC

100

Fraction by Wt: < 5%

ACGIH TLV:200 PPM

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO AIRWAY;IRRITATION-SKIN/EYE. HEADACHE,DIZZY,COMA.

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH WITH PLENTY OF WATER.REMOVE CONTAMINATED CLOTHING.INHAL:REMOVE TO FRESH AIR. CALL MD. IF NEEDED.

===== Fire Fighting Measures =====

Flash P

oint:104 F, 40 C, TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARTUS AVAILABLE FOR FIREMEN.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,SPARKS...)AVOID BREATHING VAPORS.VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE(OR COMBUSTABLE)LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE, OR WELD COATED MATERIAL W/O VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING

Supplemental Safety and Health

BOILING RANGE:155-189 C.

===== Physical/Chemical Properties =

=====

HCC:F4

Boiling Pt:B.P. Text:311-373 F

Evaporation Rate & Reference: