

CON-LUX COATINGS, INC -- TT-E-529C, CLASS A, COMP.L,#23538 YELLOW -- 8010-00-297-0585
===== Product Identification =====

Product ID:TT-E-529C, CLASS A, COMP.L,#23538 YELLOW

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0585

MSDS Number: BDVZZ

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

CAGE:6A064

=== Contr

actor Identification ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:908-287-4000

CAGE:6A064

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 20%.

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:DRYING OIL PHTHALIC ALKYD RESIN(ASVEHICLE)

(PERCENT UNKNOWN)

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 34%.

OSHA PEL:100 PPM

Ingred Name:ADDITIVES(ANTI-SKINNING AGENTS,WETTING AGENTS, SUSPENSION AGENTS, ANTIDRIER ABSORPTN AGTS

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF SKIN & EYES VAPORS -IRRIT RESP TRACT, HEADACHE, DIZZINESS.

=====
First Aid Measures
=====

First Aid:E

YES:IMMED FLUSH W/WATER AT LEAST 15 MIN SKIN:FLUSH W/PLENTY OF WATER. INHAL:REMOVE TO FRESH AIR IF IRRITATION PERSISTS, CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:105F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO*2, DRY CHEM, FOAM-FOR CLASS 1B FLAM.LIQ.FIRES.

Fire Fighting Procedures:WATER SPRAY INEFF.WATER MAY BE USED TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CNTNRS MAY EXPLODE WHEN EXPSD TO EXTREME

HEAT. DO NOT APPLY TO HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VETILATE AREA. REMOVE WITH INERT ABSRBENT AND NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES. KEEP AWAY FROM OPEN FLAMES & SPARKS.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POU

RING. AVOID

PROLONGED/REPEATED SKIN CONTACT. DOT CLASSIFICATION:COMBUSTIBLE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED CHEMICAL-MECHANICAL FILTER RESPIRATOR

Ventilation:LOCAL-USE TO KEE TLV BELOW ACCEPTABLE LIMIT.

Protective Gloves:FOR PRLNG/RPTD

Eye Protection:SFTY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT

W/CONTAMINATED CLOTHING.

Supplemental Safety and Health

=====
===== Physical/Chemical Prop
erties =====

HCC:F4

Boiling Pt:B.P. Text:315F

Vapor Pres:1

Vapor Density:4.7

Spec Gravity:1.29

Evaporation Rate & Reference:0.15 BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MILD ALIPHATIC ODOR.

Percent Volatiles by Volume:55.5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC

AL, STATE & FEDERA

REGULATIONS. DO NOT INCINERATE CLOSED CONTANERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibi

lity for the suitability of this information to their particular situation.