

RANDOLPH PRODUCTS CO. -- ZINC CHROMATE PRIMER, TT-P-1757 -- 8010-00-297-0593

=====
Product Identification
=====

Product ID:ZINC CHROMATE PRIMER, TT-P-1757

MSDS Date:08/01/1986

FSC:8010

NIIN:00-297-0593

MSDS Number: BDWCF

=== Responsible Party ===

Company Name:RANDOLPH PRODUCTS CO.

Address:PARK PLACE EAST

City:CARLSTADT

State:NJ

ZIP:07072

Info Phone Num:201-438-3700

Emergency Phone Num:201-438-370

0

CAGE:77672

=== Contractor Identification ===

Company Name:RANDOLPH PRODUCTS CO

Address:701 12TH ST

Box:830

City:CARLSTADT

State:NJ

ZIP:07072-0830

Country:US

Phone:201-438-3700

CAGE:77672

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 25-30%

Other REC Limits:0.05 MG/M3

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction

by Wt: 35-45%
Other REC Limits:100 PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALKYD RESIN
Fraction by Wt: 20-25%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:OIL MODIFIED PHENOL RESIN
Fraction by Wt: 2-7%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:MAGNESIUM SILICATE HYDRATE
CAS:1343-90-4
RTECS #:OM4360000
Fraction by Wt: 2-7%
Other REC Limits:50 PPM
OSHA PEL:N/K
ACGIH TLV:N/K

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:N/K
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF
OVEREXPOSURE SECTION .
Explanation of Carcinogenicity:ZINC CHROMATE:IARC:GROUP 1 HMN
CARC,NTP:CHROM & CERT CHROM CMPDS-KNWN CARC,ACGIH:SUSPECTED HUMAN
CARCINOGEN .
Effects of Overexposure:ACUTE:SOLVENT VAPORS MAY CAUSE DROWSINESS,
HEADACHE, DIZZINESS AND IRRITATION OF EYES, NOSE AND THROAT.
CHRONIC:N/K
Medical Cond Aggravated
by Exposure:N/K

=====
===== First Aid Measures =====
=====

First Aid:EYES:FLUSH IMMED W/LGE AMTS OF WATER FOR AT LEAST 15 MIN,
CONSULT PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. SUPPORT
BREATHING (GIVE O*2/ARTIFICIAL RESPIRATION)CONSULT PHYSICIAN.
INGESTION:CALL MD IMM EDIATELY .

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC
Flash Point:45F/7.22C
Lower Limits:N/K
Upper Limits:1.2
Extinguishing Media:SAND,

FOAM, CO*2, DRY CHEMICAL

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .AVOID BRTH VAPOR/FUME.COOL EXPOSED CONTAINERS WITH WATER TO PREVENT EXPLOSION DUE TO PRESSURE

Unusual Fire/Explosion Hazard:PREVENT FIRE, KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION,WEAR APPROVED RESPIRATOR,CONTAIN SPILL WITH INERT SUBSTANCE (SAND,DIRT),PUT MIXTURE IN CONTAINERS FOR DISPOSAL.KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT,FLAME.KEEP AWAY FROM CHILDREN. GROUND CONTAINERS AND EQUIPMENT.EMPTY CONTAINERS ARE HAZARDOUS, DO NOT CUT OR WELD

Other Precautions:N/K

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN

Ventilation:EXPLOSION PROOF EXHAUST VENTILATION AT POINT OF CONTAMINANT RELEASE

Protective Gloves:NEOPRENE

Eye Protection:CHEM WORK GOGGLES

Other Protective Equipment:COVERALLS AND BOOTS

Work Hygienic Practices:N/K

Supplemental Safety and Health

BP:110-140C.PH:NRT OF ENTRY:FPN

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:230-284F OR

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp

Temp:Decomp Text:N/K
Vapor Pres:N/K
Vapor Density:HV THN AIR
Spec Gravity:1.274
pH:N/K-FP
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:56
Corrosion Rate:

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDANTS
Stability Condition to Avoid:FLAME OR HIGH HEAT
Hazardous Decomposition Products:CARBON MONOXIDE MAY FORM WHEN BURNED.
Conditions to Avoid Polymerization:FLAME OR
HIGH HEAT

===== Disposal Considerations =====

Waste Disposal Methods:MANUFACTURER RECOMMENDS LANDFILL. DISPOSAL
METHODS MUST BE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all
liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.