View NSN Online: https://aerobasegroup.com/nsn/8010-00-297-2102

## DAVLIN PAINT CO INC -- RUBBER BASE-GRAY 16187 BTTP912 -- 8010-00-297-2102

Product ID:RUBBER BASE-GRAY 16187 BTTP912

MSDS Date:04/26/1988

FSC:8010

NIIN:00-297-2102

MSDS Number: BDWDZ === Responsible Party ===

Company Name: DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA ZIP:94702 Country:US

Info Phone Num:510-848-2863

Emergency Phone Nu m:510-848-2863

Preparer's Name: PATRICIA SHAW

CAGE:3Z268

=== Contractor Identification ===

Company Name: DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA ZIP:94702 Country:US

Phone:510-848-2863

CAGE:3Z268

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 10%

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: N-BUTYL ACET

ATE (SARA III) CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 40%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ALIPHATIC HYDROCARBON

CAS:8032-32-4 Fraction by Wt: 5.0%

Other REC Limits:(OTHER 375 PPM)

OSHA PEL:500 PPM ACGIH TLV:375 PPM

============= Hazards Identification ========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards

Acute and Chronic: MANY PETROLEUM HYDROCARBONS AND

SYNTHETIC LUBRICANTS POSE POTENTIAL HUMAN HEALTH RISKS. EXPOSURE TO LIQUIDS, VAPORS, MISTS OR FUMES SHOULD BE MINIMIZED. CHRONIC EXPOSURE MAY DAMAGE RESPIRATOR SYSTEM, LUNGS, EYES, SKIN, LIVER, SPLEEN, KIDNEYS.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CA. TO CAUSE CANCER OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Effects of Overexposure:INHAL-VAPORS CAN CAUSE NASAL AND RESPIRA TOR

IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA AND HEADACHE. SKIN-CAN CAUSE IRRITATION, DEFATTING & DERMATITIS. EYE-IRRITATION, TEARING, REDNESS & BLURRED VISION. INGESTION-CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. \* Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA. \*SUBSEQUENT VOMITING CAN CAUSE PNEUMONITIS.

First Aid:EYES-FLUSH W/WATER

FRESH AIR. APPLY ARTIFICIAL RESPIRATION OR ADMINISTER OXYGEN IF NEEDED. I NGEST-GIVE WATER OR MILK TO DRINK AND CALL FOR MEDICAL ADVICE. DO NOT MAKE PERSON VOMIT UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. IF MED ADVICE CANNOT BE OBTAINED, TAKE TO EMERGENCY HOSPITAL.
======================================
Flash Point Method:TOC Fl
ash Point:29F/-2C Lower Limits:1.0 Upper Limits:7.6 Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:USE EXTINGUISHERS DESIGNED TO EXTINGUISH NFPA FLAMMABLE LIQUID FIRE. APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE. Unusual Fire/Explosion Hazard:VAPORS FORM AN EXPLOSIVE MIXTURE WITH AIR BETWEEN LOWER AND UPPER EXPLOSIVE LIMITS WHICH CAN BE IGNITED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EX/HEA T.
========== Accidental Release Measures ===========
Spill Release Procedures:EVACUATE ALL NON-ESSENTAIL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENTILATE AREA. EQUIP EMPLOYEES WITH APPROPRIATE EQUIPMENT. DIKE AROUND SPILLED AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER U SING NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:STORE BELOW 80 DEG F IN CLOSED CONTAINER. STORE IN ORIGIN AL CONTAINER. AVOID FLAME AND HIGH TEMPERATURE. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS. Other Precautions:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL TO A SOURCE OF IGNITION & FLASHBACK. DO NOT TAKE INTERNALLY, AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MIST. KEEP AWAY FROM HEAT. GROUND ALL CONNECTIONS, CONTAINERS, ETC.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR

CLOTHING, WASH THOROUGHLY W/SOAP AND WATER. INHAL-REMOVE VICTIM TO

FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED

**GAS** 

MASK SUITABLE TO KEEP AIRBORNE MISTS AND VAPOR CONCENTRATIONS BELOW TLV. IN CONFINED AREAS USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF-CONTAINED BRE ATHING APPARATUS.

Ventilation: GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. \*

Protective Gloves:IMPERVIOUS TO PREVENT SKIN CONTACT.

Eye Protection: CHEMICAL SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING TO PRE

VENT EXPOSURE TO SKIN. HEADCAPS ARE RECOMMENDED.

Work Hygienic Practices: AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

\* VENTILATION EQUIPMENT MUST BE EXPLOSIGON PROOF.

======== Physical/Chemical Properties ===========

HCC:F3

Boiling Pt:B.P. Text:205-259F

Vapor Density:>AIR Spec Gravity:1.1

Evaporation Rate & Evaporation R

Solubility in Water: SLIGHTLY/SOLUBLE

Appearance and Odor:PIGMENTED LIQUID. STRONG SOLVENT OD

OR.

======== Stability and Reactivity Data ============

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR MONOXIDE, LOW MOLEULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

======= Disposal Considerations ============

Waste Disposal Methods: KEEP OUT OF DRAINS, SEWERS AND WATER WAYS.

DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respons

ibility for the suitability of this information to their particular situation.			