

CON-LUX COATINGS INC -- TT-P-91D TYPE 2 -- 8010-00-297-2102

=====  
Product Identification  
=====

Product ID:TT-P-91D TYPE 2  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-297-2102  
MSDS Number: BDWFB  
=== Responsible Party ===  
Company Name:CON-LUX COATINGS INC  
Address:226 TALMADGE RD  
Box:847  
City:EDISON  
State:NJ  
ZIP:08818-0847  
Country:US  
Info Phone Num:908-287-4000 / FAX 908-287-9288  
Emergency Phone Num:908-2  
87-4000  
CAGE:60189  
=== Contractor Identification ===  
Company Name:CON-LUX COATINGS INC  
Address:226 TALMADGE RD  
Box:847  
City:EDISON  
State:NJ  
ZIP:08818-0847  
Country:US  
Phone:732-287-4000  
CAGE:60189

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 29%  
OSHA PEL:100 PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 29%  
OSHA PEL:10

0 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITATION OF EYES AND SKIN CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT.

=====  
First Aid Measures  
=====

First Aid:EYES/SKIN:FLUSH WITH WATER.INHAL:MOVE TO FRESH AIR. IF IRRITATION PERSIST CALL DR.

=====  
Fire Fighting Measures  
=====

Flash Point:105

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Me

dia:CLASS B EXTINGUISHR DESIGND TO EXTINGUISH NFPA

CLASS 1 FLAME

Fire Fighting Procedures:HOH MAYBE INEFFECTIVE.HOH MAY BE USED TO PREVENT PRESSURE

Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO HOT SURFACES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING OF VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM.MECHANICAL FILTER RESPIRATOR

Ventilation:TL KEEP TLV BELO

W ACCEPTABLE LIMIT

Protective Gloves:REQUIRED

Eye Protection:EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315/157.2

Vapor Pres:2

Vapor Density:4.5

Spec Gravity:1.01

Evaporation Rate & Reference:1

Solubility in Water:NEGLIGIBLE

Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DOSPOSE IN ACCORDANCE WITH LOCAL,STATE AND  
FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants thi  
s information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.