

PRATT & LAMBERT-WICHITA DIV. -- 743-720 -- 8010-00-297-2112

=====
Product Identification
=====

Product ID:743-720

MSDS Date:01/01/1987

FSC:8010

NIIN:00-297-2112

MSDS Number: BDWFN

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Company Nam

e:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA

RTECS #:SE7525000

Fraction by Wt: 25.0%

ACGIH TLV:200

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 10.1%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS52

50000
Fraction by Wt: 8.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: < 5%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC, IRRIT AIRWAY; SKIN/EYE:IRRIT.
HEADACHE,DIZZINESS,COMA,CONFUSION.

===== First Aid Measures =====

First Aid:SKIN/EYE:FLUSH WITH PLENTY OF WATER WHILE REMOVING
CONTAMINATED CLOTHING. INHAL: REMOVE TO FRESH AIR. GIVE ARTIF.
RESP. IF NEEDED. CALL MD. IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Fla

sh Point:44 F, 7 C TCC

Lower Limits:0.9

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE
FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY
CAUSE EXPLOSION.USE WATER TO COOL CANS;FOR FIRE:FOG NOZZLES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOR
SURFACES, & ELECTRI
CAL,STATIC, OR FRICTIONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAHE OF NFPA CLASS
ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED
WHEN POURING, AVOID FREE FALL IN EXC
ESS OF A FEW INCHES, DO NOT
FLAME CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:YES, IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety
and Health

BOILING RANGE 106-143 C. EACH OF THE FOLLOWING 0.5%. TRIETHYLAMINE
MINERAL SPIRTIS AND CELLOSOLVE ACETATE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:223-290 F

Evaporation Rate & Reference:< ETHER

Appearance and Odor:YELLOW PAINT

Percent Volatiles by Volume:66.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES,HEAT, & HOT SURFACES,

SPARKS,
ELECTRICAL EQUIP.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL, STATE AND FED.
REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.