

HURON INDUSTRIES INC. -- NEOLUBE NO.1 -- 9150-00-349-7443

=====
Product Identification
=====

Product ID:NEOLUBE NO.1

MSDS Date:05/07/1986

FSC:9150

NIIN:00-349-7443

MSDS Number: BDWYW

=== Responsible Party ===

Company Name:HURON INDUSTRIES INC.

Address:3326 LAPER AVE

Box:104

City:PORT HURON

State:MI

ZIP:48060-2530

Country:US

Emergency Phone Num:313-984-4213

CAGE:03432

=== Contractor Identification

===

Company Name:HURON INDUSTRIES INC

Address:2301 16TH ST

Box:610104

City:PORT HURON

State:MI

ZIP:48061-0104

Country:US

Phone:810-984-4213

CAGE:03432

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

= Wt:94.

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PIGMENTS

= Wt:3.

Other REC Limits:10 MG/CUM AS DUST

=====
Hazards Identification
=====

Rou

tes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards Acute and Chronic: SEE SIGNS AND SYMPTOMS
Effects of Overexposure: INHALATION: EXCESSIVE INHALATION OF VAPORS OR
MIST CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, NAUSEA,
HEADACHE. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA,
VOMITING & DIARRHEA. EYE: MAY CAUSE SEVERE IRRITATION AND
DERMATITIS.

=====
First Aid Measures
=====

First Aid: INHALATION: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR; IF
BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS
STOPPED, GIVE ARTIFICIAL RESPIRATION & SEEK MEDICAL ATTENTION
IMMEDIATELY. INGESTION: KEEP INDIVIDUAL CALM AND SEEK
MEDICAL ATTENTION IMMEDIATELY. EYE: FLUSH EYES WITH WATER & SEEK
MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING & LAUNDRY.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC

Flash Point: =11.1C, 52.F

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING SUPPLY.

Unusual Fire/Explosion Hazard: KEEP AWAY FROM SPARKS, OPEN FLAMES, OR
OTHER SOURCES OF IGNITION.

=====
Accidental Release Measures
=====

Spill Release Procedures: APPLY ABSORBENT MATERIAL AND TRANSFER TO
CONTAINERS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: IF THE TLV OF THE PRODUCT IS EXCEEDED, A
MECHANICAL OR SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED.

Ventilation: PROVIDE SUFFICIENT LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW
TLV(S).

Protective Gloves: WEAR SOLVENT RESISTANT GLOVES.

Eye Protection: WEAR CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: AVOID INHALATION OF MISTS OR VAPORS.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER

UFACTURER.

===== Physical/Chemical Properties =====

HCC:F2

Spec Gravity:0.79

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREY FLUID, SHARP ODOR

Percent Volatiles by Volume:94

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE & CARBON MONOXIDE

===== Disposal

Considerations =====

Waste Disposal Methods:CONSULT WITH FEDERAL, STATE & LOCAL WASTE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.