

FISKE BROTHERS REFINING COMPANY -- LUBRIPLATE 105 -- 9150-00-392-1670

=====
Product Identification
=====

Product ID:LUBRIPLATE 105

MSDS Date:11/01/1985

FSC:9150

NIIN:00-392-1670

MSDS Number: BDXLH

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING COMPANY

Address:1500 OAKDALE AVE, STATION "A"

Box:8038

City:TOLEDO

State:OH

ZIP:43605

Country:US

Info Phone Num:419-691-2491

Emergency Phon

e Num:419-691-2491

Preparer's Name:O.F. KUHLMAN

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM SOAP (THICKENER)(8-12%)

Fracti

on by Wt: 8.0%
Other REC Limits:NONE SPCIFIED

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: 90.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9293

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 2.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inh
Exposure: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED CONTACT WITH
SKIN MAY CAUSE IRRITATION.
Explanation of Carcinogenicity:NO DATA AVAILABLE.
Effects of Overexposure:SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE
IRRITATION; EYES:MAY CAUSE IRRITATION ON CONTACT;
INHALATION/INGESTION: PRODUCT HAS LOW ORDER OF TOXICITY.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

==
=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES OR UNTIL
IRRITATION SUBSIDES.IF IRRITATION PERSISTS,CONSULT DOCTOR;
SKIN:REMOVE ANY CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP &
WARM WATER.W ASH OFF SKIN;INHALATION:IF OVERCOME BY VAPOR FROM HOT
PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE;INGESTION:CALL PHYSICIAN
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

==

Flash Point Method:COC

Flash Point:360F/316C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL,WATER SPRAY.

Fire Fighting Procedures:USE SCBA WITH PROTECTIVE CLOTHING AS FOR LUBRICATING GREASE

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE,WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT.KEEP PETROL

EUM PRODUCTS OUT OF

SEWERS & WATERCOURSES.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS & WA TER COURSES.KEEP WASTE IN COVERED DRUM PENDG INSTR

===== Handling and Storage =====

Handling and Storage Precautions:USE GOOG HYGIENE PRACTICES FOR LUBRICATING GREASE AND OIL. DO NOT STORE ABOVE 150F TO INSURE PHYSICAL STABILITY

Other Precautions:AVOID EYES & SKIN EXPOSURE.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 550F/288C

Vapor Pres:5

Spec Gravity:0.89-0.93

Evaporation Rate & Reference: