

PORTER PAINT CO -- 24771 EPOXY FINISH OFF WHITE -- 8010-00-402-0953

=====
Product Identification
=====

Product ID:24771 EPOXY FINISH OFF WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-402-0953

MSDS Number: BDXRX

=== Responsible Party ===

Company Name:PORTER PAINT CO

Address:400 S 13TH ST

City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

CAGE:50411

=== Contractor Identification ===

Company Name:COUR

TAULDS COATINGS INC

Address:400 S 13TH STREET

Box:City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

Phone:502-588-9651

CAGE:50411

=====
Composition/Information on Ingredients
=====

Ingred Name:AROMATIC HYDROCARBON (VAP PRES 9.5)

Fraction by Wt: 5%

ACGIH TLV:100PPM (MFR)

Ingred Name:AROMATIC HYDROCARBON (VAP PRES 3)

Fraction by Wt: 5%

ACGIH TLV:100 PPM (MFR)

Ingred Name:KETONE (TYPE NOT SPECIFIED) VAP PRES 4

Fraction by Wt: 10%

ACGIH TLV:100PPM (MFR)

Ingred Name:ALCOHOL (T

TYPE NOT SPECIFIED)

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION: IRRIT,NAUSEA,DIZZY,VOMITING. EYE:
IRRIT,CORNEAL INJURY. SKIN: IRRIT.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE FROM EXPOSURE,RESTORE BREATH,NOTIFY
PHYSICIAN. EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN:
REMOVE CONTAMINAT CLOTH,WASH AFFECTED AREA, CONTACT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:85F PMCC
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL,FOAM
Fire Fighting Procedures:WATER SPRAY TO COOL CONT,WEAR SELF CONT BREATH
APP.
Unusual Fire/Explosion Hazard:HEAT CAUSES PRESSURE BUILD UP IN CLOSED
CONTAINERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT
SURFACE AND ELECTRICAL,STATIC OR FRICTION SPARKS) AVOID BREATH
VAPORS. VE
CONTAMINATE AREA. REMOVE WITH INERT ABSORBENT AND USE
NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. KEEP CANS
CLOSED WHEN NOT IN USE. STORE LARGE QUANTITIES IN BLDG DESIGNED FOR
CLASS 1C FLAMMABLE
Other Precautions:DO NOT TAKE INTERNALLY. CLEAN HANDS BEFORE
SMOKING,EATING AND AFTER USING. GROUND CONT BEFORE POURING. LIMIT
FREE FALL TO FEW INCHES. DO NOT FLAME CUT,BRAZE OR WELD W/
OUT
APPRVD RESP OR VENT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:GENERAL OR LOCAL IN ACCORD WITH EXPOSURE OF CONCERN
Protective Gloves:YES
Eye Protection:CHEM GOGGLE
Other Protective Equipment:COVER-ALLS
Supplemental Safety and Health
3 PART KIT,PRIMER,FINISH COAT AND EPOXY CONVERT.KEY1:J1.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:262-350F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:53.8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF
IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (pro

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.