

PORTER PAINT CO -- 24770 EPOXY PRIMER ORANGE -- 8010-00-402-0953

===== Product Identification =====

Product ID:24770 EPOXY PRIMER ORANGE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-402-0953

MSDS Number: BDXRY

=== Responsible Party ===

Company Name:PORTER PAINT CO

Address:400 S 13TH ST

City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

CAGE:50411

=== Contractor Identification ===

Company Name:COURTAULDS

COATINGS INC

Address:400 S 13TH STREET

Box:City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

Phone:502-588-9651

CAGE:50411

===== Composition/Information on Ingredients =====

Ingred Name:AROMATIC HYDROCARBON (VAP PRES 9.5)

Fraction by Wt: 5%

ACGIH TLV:100PPM (MFR)

Ingred Name:AROMATIC HYDROCARBON (VAP PRES 3)

Fraction by Wt: 5%

ACGIH TLV:100PPM (MFR)

Ingred Name:KETONE (TYPE NOT SPECIFIED) (VAP PRES 4)

Fraction by Wt: 15%

ACGIH TLV:100PPM (MFR)

Ingred Name:LEAD COMPOUNDS

Fraction by Wt: 15%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3 (PB);8990

Ingred Name:CHROMIUM (VI) OXIDE  
CAS:1333-82-0  
RTECS #:GB6650000  
Fraction by Wt: 3%  
OSHA PEL:C, 0.1 MG/M3 (CRO3)  
ACGIH TLV:0.05 MG/M3(CR); 8990

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALATION: IRRIT,NAUSEA,DIZZY,VOMITING. EYE:  
IRRIT,CORNEAL INJURY. SKIN: IRRIT.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE  
FROM EXPOSURE,RESTORE BREATH,NOTIFY  
PHYSICIAN. EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN.SKIN: REMOVE  
CONTAMINAT CLOTH,WASH AFFECTED AREA,CONTACT PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point:85F (PMCC)  
Lower Limits:1  
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM  
Fire Fighting Procedures:WATER SPRAY TO COOL CONT,WEAR SELF CONT BREATH  
APP.  
Unusual Fire/Explosion Hazard:HEAT CAUSES PRESSURE BUILD UP IN CLOSED  
CONTAINERS

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT  
SURFACE AND ELECTRICAL,STATIC OR FRICTION SPARKS) AVOID BREATH  
VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND USE  
NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. KEEP CANS  
CLOSED WHEN NOT IN USE. STORE LARGE QUANTITIES IN BLDG DESIGNED FOR

CLASS 1C FLAMMABLE

Other Precautions:DO NOT TAKE INTERNALLY. CLEAN HANDS BEFORE SMOKING,EATING AND AFTER USING. GROUND CONT BEFORE POURING. LIMIT FREE FALL TO FEW INCHES. DO NOT FLAME CUT,BRAZE OR WELD W/OUT APPROVD RESP OR VENT

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN

Ventilation:GENERAL OR LOCAL IN ACCORD WITH EXPOSURE OF CONCERN

Protective Gloves:YES

Eye Pro

tection:CHEM GOGGLE

Other Protective Equipment:COVER-ALLS

Supplemental Safety and Health

3 PART KIT,PRIMER,FINISH COAT AND EPOXY CONVERT.KEY1:J1.

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:276-350F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:48.3

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,P6,  
CRO3

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.