View NSN Online: https://aerobasegroup.com/nsn/8010-00-402-0953

COOD PAINT AND VARNISH CO. -- MIL-C-4556D TYPE G PRIMER -- 8010-00-402-0953

Product ID:MIL-C-4556D TYPE G PRIMER MSDS Date:01/01/1985 FSC:8010 NIIN:00-402-0953 **MSDS Number: BDXSG** === Responsible Party === Company Name: COOD PAINT AND VARNISH CO. Address:919 E 14TH AVE Box:389 City:KANSAS CITY State:MO ZIP:64116-3703 Country:US CAGE:LO321 === Contractor Identifica tion === Company Name: COOD PAINT AND VARNISH CO. Address:919 E 14TH AVE Box:389 **City:KANSAS CITY** State:MO ZIP:64116-3703 Country:US CAGE:LO321 Company Name: COOK PAINT AND VARNISH CO Address:919 E 14TH AVE Box:389 City:KANSAS CITY State:MO ZIP:64116-3703 Country:US Phone:816-471-1755 CAGE:72225

Ingred Name:EPOXY RESIN Fraction by Wt: 25%

Ingred Name:BUTYL ALCOHOL RTECS #:EO0140000 Fraction by Wt: 15% ACGIH TLV:S,C50PPM

Ingre

d Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT) CAS:8002-05-9 RTECS #:SE7449000 Fraction by Wt: 10% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 8990

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 5% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD COMPOUNDS OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.15 MG/M3 (PB);8990

====

Effects of Overexposure:INHALATION:ANESTH,IRRIT OF RESP TRACT,CNS DEPRES,HEADACHE,DIZ,STAG,UNCON,COMA.SKIN/EYE CONT:IRRIT

First Aid:INHALAITON:REMOVE FROM EXPOSURE,RESTORE BREATH,NOTIFY A MD EYE CONT: FLUSH WITH WATER FOR 15 MIN,NOTIFY A MD.SKIN CONT:WASH WITH WATER,REMOVE CONTAMINATED CLOTH,CONSULT A MD,INGESTION:DO NOT INDUCE VO MITING CALL A DR IMMED.DISCARD CONTAM SHOES.

======= Fire

Flash Point:81F SETAFLASH Extinguishing Media:CARBON DIOXIDE,DRY CHEM,FOAM,CLASS B EXTINGUISHER Fire Fighting Procedures:FULL EQUIP INCL SELF CONT BREATH,FOG NOZZEL TO COOL CANS Unusual Fire/Explosion Hazard:PRODUCT/RESIDUE CAN IGNITE EXPLOSIVELY,NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS

. VENTILATE AREA.CONTAIN AND REMOV WITH INERT ABSORBENT AI	ND
NON-SPARKING TOOLS	

Handling and Storage Precautions:DO NOT STORE AT TEMPS ABOVE 120F.KEEP AWAY FROM SPARKS,HEAT,OPEN FLAMES.GROUND CONTAINERS WIHEN POURING.AVOID FREE FALL OF LIQUIDS
Other Precautions:WASH HANDS AFTER USING AND BEFORE EATING OR SMOKING.KEEP OUT OF REACH OF CHILDREN.DO NOT USE ON TOYS,FURNITURE OR SURFACES WHICH MAY BE CHEWED BY CHI
LDREN.KEEP CONT CLOSED AND UPRIGHT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN Ventilation:LOCAL EXHAUST Protective Gloves:YES Eye Protection:GLASSES WITH SPLASH GUARD Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT Supplemental Safety and Health MANUF CODE 920-Y-131. THIS IS A 2-COMPONENT SYSTEM, THE MIXTURE WILL HAVE HAZARDS OF BOTH. KEY1:J1.

======

Boiling Pt:B.P. Text:230-340F Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:54

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:FUMES MAY CONTAIN CARBON MONOXIDE AND OXIDE OF NITROGEN Conditions to Avoid Polymerization:ELEVATED TEMPES,EXOTHERMS WHEN CURED

\_\_\_\_\_

## Waste Disposal Methods:DISPOSE OF IAW LOCAL,STATE AND FED REGS.DO NOT INCINERATE CLOSED CONTAINERS.INCINERATE IN APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.