

JOTUN-BALTIMORE COPPER PAINT CO -- F-154,R=3.6,DK GRAY TOPCOAT 5436,MFR N-14 --  
8010-00-410-8465

=====  
Product Identification  
=====

Product ID:F-154,R=3.6,DK GRAY TOPCOAT 5436,MFR N-14

MSDS Date:01/01/1985

FSC:8010

NIIN:00-410-8465

Kit Part:Y

MSDS Number: BDYDD

==== Responsible Party ====

Company Name:JOTUN-BALTIMORE COPPER PAINT CO

Emergency Phone Num:301-539-0045

CAGE:85319

==== Contractor Identif

ication ====

Company Name:JOTUN-BALTIMORE COPPER PAINT CO.

CAGE:85319

=====  
Composition/Information on Ingredients  
=====

Ingred Name:EPOXY RESIN

Fraction by Wt: 43.6%

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)

CAS:2426-08-6

RTECS #:TX4200000

Fraction by Wt: 5.9%

OSHA PEL:50 PPM

ACGIH TLV:25 PPM; 9293

Ingred Name:AROMATIC HYDROCARBON,EXXON AROMTAIC 100.FORMERLY SOLVESSO  
100,CONTAINS ALKYLATED BENZENE.

Fraction by Wt: 24.7%

ACGIH TLV:100PPM, MFR

Ingred Name:MAGNESIUM SLICAT

E

Fraction by Wt: 24.8%

Ingred Name:CASTOR OIL DERIVATIVE

RTECS #:FI4100000

Fraction by Wt: 1.0%

=====  
Hazards Identification  
=====

Effects of Overexposure:INH: ANESTH. IRRIT RESP TRACT. ACUTE CNS

DEPRESS: HDACHE, DIZZ, UNCONSC, COMA. SKIN/EYE IRRIT.

=====  
First Aid Measures  
=====

First Aid:INH: REMOVE FROM EXPOSURE. RESTORE BRTH. KEEP WARM/QUIET.

CALL MD. EYES: FLUSH IMMED W/LG AMT WATER 15 MIN. TAKE TO MD. SKI

N:  
WASH W/WATER. REMOVE CONTAM CLOTHING. CONSULT MD.

=====  
Fire Fighting Measures  
=====

Flash Point:115F PMCC  
Lower Limits:1.2  
Extinguishing Media:CARBON DIOXIDE, DRY CHEM OR FOAM  
Fire Fighting Procedures:FULL PROT EQUIP & SELF-CNTND BRTH.WATER-COOL  
CNTNR W/FOG NOZ  
Unusual Fire/Explosion Hazard:CLOSE CNTNR TIGHT. ISOLATE FROM IGNIT  
SOURCES. CLOSED CNTNR MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNIT. AVOID BRTHNG  
VAPORS. VENT AREA. CONTAIN & REMOVE W/INERT ABSORBENT &  
NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. KEEP CLOSURE  
TIGHT. DO NOT STORE OR USE NEAR HEAT, SPARKS, FLAME.  
Other Precautions:DO NOT GET IN EYES. AVOID PROLONGED CNTCT W/SKIN &  
BRTHNG OF VAPORS/SPRAY MIST. DO NOT TAKE INTERN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPRVD  
Ventilation:DILUTION OR LOCAL TO KEEP VAPORS BELOW TLV  
Protective Gloves:SOLVENT RESIST  
Eye Protection:SAFETY W/SPLASH GUARDS  
Other Protective Equipment:USE PROT CREAM WHERE SKIN CNTCT LIKELY  
Supplemental Safety and Health  
VAP DNSTY HEAVIER THAN AIR. AROMATIC HYDROCARBON SOLVLESSO 100  
CONTAINING >92% ALKYLATED BENZENES, MAINLY C\*8 & C\*10. WT/GAL: 10.2  
LB.KEY1:F4.

=====  
Physi

cal/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-344F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:34.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HI TEMPS & CONTAM W/FOREIGN MATLS

Hazardous Decomposition Products:HAZ FUMES WHEN HEATED DECOMP

===== Disposal Considerations =====

Waste Disposal Methods:DIS

POSE IAW LOCAL, STATE, FED REG. INCINERATE IN

APPRVD FACILITY. DO NOT INCINERATE CLOSED CNTNRS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.