

APPLIED PLASTICS CO.,INC -- APCO HARDENER B (FOR USE WITH APCO 5313) -- 8040-00-426-9653

=====
Product Identification
=====

Product ID:APCO HARDENER B (FOR USE WITH APCO 5313)

MSDS Date:01/01/1985

FSC:8040

NIIN:00-426-9653

MSDS Number: BDYQH

=== Responsible Party ===

Company Name:APPLIED PLASTICS CO.,INC

Emergency Phone Num:213-322-8050

CAGE:05866

=== Contractor Identification ===

Company Name:AP

PLIED PLASTICS CO

Address:612 E FRANKLIN AVE

Box:City:EL SEGUNDO

State:CA

ZIP:90245

Country:US

CAGE:05866

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC AMINE

Fraction by Wt: 100%

=====
Hazards Identification
=====

Effects of Overexposure:SEVERE SKIN/EYE BURNS. IRRITATION OF
RESPIRATORY TRACT,MAY CAUSE SENSITIZATION.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WIT

H WATER 15 MIN IMMED MEDICAL ATTN. SKIN: WASH

WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO
NOT INDUCE VOMITING,FORCE MILK,WATER OR DILUTE VINEGAR & GET
MEDICAL HELP IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point:210F/98C (COC)

Extinguishing Media:WATER,DRY CHEMICAL

=====
Accidental Release Measures
=====

Spill Release Procedures:USE APPROPRIATE SAFETY EQUIPMENT,WASH DOWN
WITH COPI

OUS AMOUNTS OF WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHTLY SEALED CONTAINERS. FOR INDUSTRIAL USE ONLY.

Other Precautions:USE GOOD VENTILATION. REMOVE & CLEAN CONTAMINATED CLOTHING BEFROE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:LOCAL/GENERAL EXHAUST

Protective Gloves

:RUBBER/PLASTIC

Eye Protection:GOGGLES,FACE SHIELD

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. PRPER BENCH COVERS.

Supplemental Safety and Health

PART B OF A 2 PART KIT.KEY1:N1.

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:200C/392F

Vapor Pres:0.3

Vapor Density:3.48

Spec Gravity:0.95

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR WATERLIKE LIQUID-AMMONIACAL ODOR

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACID,CHLORINATED HYDROCARBONS

Conditions to Avoid Polymerization:MIXING WITH LIQUID EPOXY RESINS IN >1 LB. MASSES.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DILUTE WITH WATER AND CONTAIN. STANDARD INDUSTRIAL WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by eleme

nts of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.