

E.I. DU PONT DE NEMOURS & CO., INC. -- 70S, DUCO PRIMER, GRAY -- 8010-00-430-0193

=====
Product Identification
=====

Product ID:70S, DUCO PRIMER, GRAY

MSDS Date:01/01/1985

FSC:8010

NIIN:00-430-0193

MSDS Number: BDYQN

=== Responsible Party ===

Company Name:E.I. DU PONT DE NEMOURS & CO., INC.

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19899

Country:US

Info Phone Num:800-441-75

15

Emergency Phone Num:800-441-7515

CAGE:18773

=== Contractor Identification ===

Company Name:E.I. DU PONT DE NEMOURS & CO., INC.

CAGE:18773

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 3%

OSHA PEL:S,200PPM/250STEL

AC

GIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 17%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)
CAS:8002-05-9
RTECS #:SE7449000
Fraction by Wt: 3%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 8990

Ingred Name:ALIPHATIC KETONE
Fraction by Wt: 11%
ACGIH TLV:50 PPM, MFR

Ingred Name:ALIPHATIC ESTER
R
Fraction by Wt: 5%
ACGIH TLV:150 PPM, MFR

===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA,IMPAIRMENT OF REACTION TIME &
COORDINATION.

===== First Aid Measures =====

First Aid:INH:MOVE TO FRESH AIR TO IMPROVE BREATHING. SKIN:WASH W/SOAP
& WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE.
EYES:FLUSH W/WATER AT LEAST 15 MINS, CALL MD.

===== Fire Fighting Meas

ures =====

Flash Point:20-73F CC

Lower Limits:1.3

Upper Limits:36.5

Extinguishing Media:FOAM, CO*2, DRY CHEMICAL

Fire Fighting Procedures:H*2O FOG NOZZLE:USE TO COOL CLSD CNTNR,PRVNT
PRESS BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID PROLONGED CONTACT W/SKIN & BREATHING OF
VAPOR. REMOVE SOURCES OF IGNITION. REMOVE W/INERT ABSORBENT.
VENTILATE AREA.

===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN
FLAME. CLOSE CONTAINER AFTER EACH USE. DO NOT STORE ABOVE 120F,49C.

Other Precautions:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR
SMOKING. OBSERVE LABEL PRECAUTIONS. CONTAINERS SHOULD BE GROUNDED
WHEN POURING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD IF AIR CONTAMINANT CONTROLK IS
NOT FEASIBLE.

Ventilation:LOC & MECH ADEQ

UATE TO KEEP BELOW TLV/LEL.REMOVE IGN
SOURCES

Protective Gloves:PRLNGD/RPTD CNT

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:USE APPROPRIATE INDUSTRIAL HYGIENE
PRACTICES.

Supplemental Safety and Health

ADDTNL INGRED:ALIPHATIC ALCOHOL,6%,TLV=400 PPM,MFR. BP:54-142C. FL
PT:-6.7-23C CC. BP IS APPROX RANGE. VAP PRESS & VAP DENSITY ARE
FOR PRINCIPAL SOLVENT. % OF INGREDIENTS IS APPROX.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.

P. Text:129-287F

Vapor Pres:22

Vapor Density:3.10

Spec Gravity:1.174

Evaporation Rate & Reference: