View NSN Online: https://aerobasegroup.com/nsn/8010-00-437-6757

DEVOE & RAYNOLDS, INC -- MD8734, GREEN PRIMER, MIL-P-24441/1 PART B -- 8010-00-437-6757

Product ID:MD8734, GREEN PRIMER, MIL-P-24441/1 PART B

MSDS Date:01/01/1987

FSC:8010

NIIN:00-437-6757

Kit Part:Y

MSDS Number: BDYXQ === Responsible Party ===

Company Name: DEVOE & RAYNOLDS, INC

Address:2625 DURAHART ST

City:RIVERSIDE

State:CA

ZIP:92507-2606

Country:US

CAGE:EO55

=== Contractor Identification ===

Company Name: DEVOE & RAYNOLDS CO, INC.

Box:7600 CAGE:EO559

Company Name: DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:2625 DURAHART ST

Box:City:RIVERSIDE

State:CA

ZIP:92507-2606 Country:US CAGE:70506

======= Composition/Information on Ingredients ========

Ingred Name: PIGMENTS Fraction by Wt: 24.7%

Ingred Name: EPOXY (VEHICLE)

Fraction by Wt: 50.3%

Ingred Name: NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt:

| ========== Hazards Identification ============   |    |
|--|----|
| Effects of Overexposure:INHAL: HEADACHE, NAUSEA, DIZ. SKIN: PRLNGD/RPTD CONTACT MAY CAUSE IRRIT. AVOID EYE CONTACT.  |    |
| ======================================   |    |
| First Aid:SKIN: IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER REMOVE CONTAMINATED CLOTHING. EYE: IMMEDIATELY FLUSH W/WATER FOR AT LEA 15 MIN. CALL MD. INHAL: MOVE TO FRESH AIR.  | ST |
| =========== Fire F ighting Measures ====================================   |    |
| Flash Point:102 PMCC Lower Limits:1.0 Extinguishing Media:CO*2, DRY CHEMICAL Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE   |    |
| ========= Accidental Release Measures ===========  |    |
| Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION SOURCES IN IMMEDIATE AREA. AVOID CONTACT W/LIQUID.  |    |
| ======================================   |    |
| Handling and Storage Precaut ions:DO NOT STORE AT ELEVATED TEMPERATURES.  VENTILATION - USE SPARK PROOF EQUIPMENT.  Other Precautions:CLOSE CONTAINERS AFTER USE. DOT CLASSIFICATION: FLAMMABLE.                                 |    |
| ====== Exposure Controls/Personal Protection ========  |    |
| Respiratory Protection:CONFINED AREAS - USE NIOSH/MSHA APPR RESPIRATOR DEVICE  Ventilation:KEEP CONC BELOW TLV. ADEQUATE VENTILATION IS REQUIRED.  Protective Gloves:SOLVNT RESIST  Eye Protective Equipment:NORMAL PROTECTIVE C |    |
| OIDECPIDIECIVE FALIAMENTINORIVIAL PROTECTIVE (.  |    |

25.0%

OSHA PEL:100 PPM

| LOTHING   |
|---|
| Supplemental Safety and Health  |
| PART B OF A TWO PART KIT, WHICH CONTAINS DIFFERENT CLASSES AND LABELS |
| OF HAZARDOUS MATERIALS, 5 GAL. COMPONENT B.KEY1:F4.                   |
| ========= Physical/Chemical Properties ===========                    |
| HCC:F4  |
| Boiling Pt:B.P. Text:315 TO 349F                                      |
| Vapor Pres:30   |
| Spec Gravity:1.19   |
| Evaporation Rate & Dr. Reference: 0.2 N-BUTYL ACET                    |
| Solubility in Water:NEGLIGIBLE  |
| Appearance and Odor:GREEN, MOBILE, CONTAINING VOLATILE LIQUIDS        |
| Percent Volatiles by Volume:34.7                                      |
| ==========  |
| === Stability and Reactivity Data ===========                         |
| Stability Indicator/Materials to Avoid:YES                            |
| OXIDIZING MATERIALS, RUBBER SOFTENS.                                  |
| Hazardous Decomposition Products:CO, CO*2                             |

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM IGNITION SOURCES. (MFG REC)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.