

JOTUN-BALTIMORE COPPER PAINT CO -- F-150, 5429 GREEN PRIMER, MFR CODE G-452 --
8010-00-437-6757

=====
Product Identification
=====

Product ID:F-150, 5429 GREEN PRIMER, MFR CODE G-452

MSDS Date:01/01/1987

FSC:8010

NIIN:00-437-6757

Kit Part:Y

MSDS Number: BDYXS

=== Responsible Party ===

Company Name:JOTUN-BALTIMORE COPPER PAINT CO

Emergency Phone Num:301-539-0045

CAGE:85319

=== Contractor Identific

ation ===

Company Name:JOTUN-BALTIMORE COPPER PAINT CO.

CAGE:85319

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 28.1%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE/EPOXY ADDUCT

Fraction by Wt: 17.6%

Ingred Name:RATTY AMIDOAMINE ADDUCT

Fraction by Wt: 1.7%

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Frac

tion by Wt: 8.4%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 1.7%
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

=====
Hazards Identification
=====

Effects of Overexposure:INH: ANESTHETIC. IRRIT RESP TRACT. ACUTE CNS
DEPRESS: HDACHE, DIZZ, UNCON, COMA. SKIN/EYE: IRRIT.

=====
First Aid Measures
=====

First Aid:INH: REMOVE FROM EX
POSURE. RESTORE BRTH. KEEP WARM/QUIET,
CALL MD. EYES: FLUSH IMMED W/LG AMT WATER 15 MIN. TAKE TO MD. SKIN:
WASH W/WATER. REMOVE CONTAM CLOTHING. CONSULT MD.

=====
Fire Fighting Measures
=====

Flash Point:99F PMCC
Lower Limits:1.4
Extinguishing Media:CARBON DIOXIDE, DRY CHEM, FOAM
Fire Fighting Procedures:FULL PROT EQUIP, SELF-CNTND BRTH. WATER-COOL
CNTNR W/FOG NOZ
Unusual Fire/Explosion Hazard:CLOSE CNTNR TIGHT, ISOLATE FROM IGNIT
SOURCES. CLOS
ED CNTNR MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BRTHNG
VAPORS. VENT AREA. CONTAIN & REMOVE W/INERT ABSORBENT & NON
SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. KEEP CLOSURE
TIGHT. DO NOT STORE OR USE NEAR HEAT, SPARKS OR FLAME.
Other Precautions:DO NOT G

ET IN EYES. AVOID PROLONGED CONTACT WITH SKIN,
BREATHING OF VAPOR SPRAY MIST. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH/MSHA APPROVED
Ventilation: DILUTION OR LOCAL TO KEEP VAPORS BELOW TLV
Protective Gloves: SOLVENT RESISTANT
Eye Protection: SAFETY WITH SPLASH GUARDS
Other Protective Equipment: USE PROTECTIVE CREAM WHERE SKIN CONTACT IS LIKELY
Supplemental Safety and Health Information: USE AS PART A OF A TWO PART KIT. THAT CONTAINS DIFFERENT CLASSES AND LABELS OF
HAZARDOUS MATERIALS. KEY1:FR.

===== Physical/Chemical Properties =====

HCC: F4
Boiling Point: 241-247°F
Vapor Pressure: 4 mmHg
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 48.5

===== Stability and Reactivity Data =====

Stability Indicator/ Materials to Avoid: YES
Stability Condition to Avoid: HIGH TEMPERATURES & CONTAMINATION WITH FOREIGN MATERIALS
Hazardous Decomposition Products: HAZARDOUS FUMES WHEN HEATED DECOMPOSE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.