

AIRCO DIV.OF THE BOC GROUP,INC. -- HYDROGEN-REFRIGERATED GAS -- 6830-00-474-5789

=====
Product Identification
=====

Product ID:HYDROGEN-REFRIGERATED GAS

MSDS Date:07/01/1986

FSC:6830

NIIN:00-474-5789

MSDS Number: BDZSL

=== Responsible Party ===

Company Name:AIRCO DIV.OF THE BOC GROUP,INC.

Address:575 MOUNTAIN AVE.

City:MURRY HILL

State:NJ

ZIP:07974-2006

Info Phone Num:201-464-8100

Emergency Phone

Num:201-464-8100 CHEMTREC 800-424-9300

CAGE:LO430

=== Contractor Identification ===

Company Name:AIRCO DIV.OF THE BOC GROUP,INC.

Address:575 MOUNTAIN AVE.

Box:City:MURRY HILL

State:NJ

ZIP:07974-2006

Phone:201-464-8100

CAGE:LO430

Company Name:BOC GROUP INC THE, BOC GASES DIV

Address:575 MOUNTAIN AVE

Box:City:NEW PROVIDENCE

State:NJ

ZIP:07974-1209

Country:US

Phone:908-464-8100

CAGE:6J576

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROGEN

CAS:1333-74-0

RTE

CS #:MW8900000
Fraction by Wt: 99.999%
Other REC Limits:SEE SUPP DATA

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HYDROGEN IS NON-TOXIC AND IS DANGEROUS
PHYSIOLOGICALLY AS AN ASPHYXIANT. THE CRYOGENIC LIQUID WILL FREEZE
TISSUES IF IN CONTACT WITH SKIN OR EYES.
Effects of Overexposure:INHALATION:EFFECTS OF OXYGEN
STARVAT
ION,DROWSINESS,LOSS OF CONSCIOUSNESS. SKIN
CONTACT-FROSTBITE:CHANGE OF COLOR TO GRAY OR WHITE,POSSIBLY WITH
BLISTERING.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:INHALED:REMOVE TO FRESH AIR.GIVE ARTIFICIAL RESPIRATION OR
OXYGEN AS NEEDED.GET MEDICAL ATTENTION.FROSTBITE:FLUSH AFFECTED
AREA WITH LUKEWARM WATER.DO NOT USE HOT WATER.GET PROMPT MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:GAS
Lower Limits:4.0
Upper Limits:74.5
Extinguishing Media:WATER,CARBON DIOXIDE,DRY CHEMICAL
Fire Fighting Procedures:IF POSSIBLE, STOP FLOW OF HYDROGEN. COOL
SURROUNDING CONTAINERS WITH WATER. HYDROGEN BURNS WITH LITTLE
RADIATED HEAT AND AN ALMOST INVISIBLE FLAME.
Unusual Fire/Explosion Hazard:HYDROGEN IS LIGHTER THAN AIR AND WILL
COLLECT NEAR CEILINGS. VENTILATE UPPER AREAS TO PREVENT FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL AND ELIMINATE IGNITION
SOURCES. USE APPROPRIATE PROTECTIVE EQUIPMENT.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT PERMIT SMOKING OR OPEN FLAMES
IN STORAGE AREA. STORE IN WELL VENTILATED AREA. SEE CGA PAMPHLETS
G-5,P-12 AND OSHA 1910 SUBPART H.
Other Precautions:USE ONLY NON-SPARKING OR EXPLOSION PROOF EQUIPMENT.
GROUND A

ALL FIXTURES AND EQUIPMENT. FEDERAL LAW PROHIBITS SHIPPING A VESSEL NOT FILLED BY THE OWNER WITHOUT HIS EXPRESS (WRITTEN) CONSENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR EMERGENCY:USE ESCAPE AIR SUPPLY OR SELF CONTAINED BREATHING APPARATUS.

Ventilation:HOOD WITH FORCED VENTILATION,AND OTHER LOCAL/GENERAL EXHAUST TO PREVENT ACCUMULATIONS ABOVE LEL.

Protective Gloves:LOOSE FITTING,INSULATED

Eye Protection:SPLASH GOGGLES/GLASSE
S PLUS FACE SHIELD

Other Protective Equipment:SAFETY SHOES,SAFETY SHOWER

Work Hygienic Practices:USE NORMAL PERSONAL HYGIENE PRACTICE.

Supplemental Safety and Health

MFR RECOMMENDS OXYGEN LEVEL BE MAINTAINED AT 18% OR MORE WHICH IS EQUAL TO A PARTIAL PRESSURE OF 135MM OF HYDROGEN.

===== Physical/Chemical Properties =====

HCC:G2

Boiling Pt:B.P. Text:-423F/-252C

Melt/Freeze Pt:M.P/F.P Text:-435F/-259C

Spec Gravity:0.071(AIR=1)

Solubility in Water:VERY SLIGHT

Appearance

Color and Odor:COLORLESS,ODORLESS GAS OR LIQUID **GAS DENSITY =
0.1005209 LB/CUFT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF UNUSED HYDROGEN.
RETURN TO MFR FOR PROPER DISPOSAL.

Disclaimer (provided with this informat

ion by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.