

SHELL OIL COMPANY -- AEROSHELL(R) GREASE 14 (MIL-G-25537;MIL-G-25537C) --
9150-00-478-0055

===== Product Identification =====

Product ID:AEROSHELL(R) GREASE 14 (MIL-G-25537;MIL-G-25537C)

MSDS Date:07/09/1991

FSC:9150

NIIN:00-478-0055

MSDS Number: BDZVF

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:U

S

Info Phone Num:713-241-4819/4141/2252 FAX -6511

Emergency Phone Num:713-473-9461/800-424-9300(CHEMTREC)

Preparer's Name:J. C. WILLETT

CAGE:54527

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

Company Name:MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

Box:City:GRETNA

State:LA

ZIP:70053

Country:US

Phone:504-362-3232, OR 800-535-4095

CAGE:2

7978
Company Name:SALATHE OIL CO INC
Address:2226 PETERS RD
Box:City:HARVEY
State:LA
ZIP:70058

Country:US
Phone:504-366-4542
CAGE:0T5C6
Company Name:SHELL OIL CO
Address:1 SHELL PLAZA
Box:2463
City:HOUSTON
State:TX
ZIP:77001
Country:US
Phone:713-473-9461/800-424-9300(CHEMTREC)
CAGE:93508

Company Name:SHELL OIL COMPANY
Address:Box:2463
City:HOUSTON
State:TX
ZIP:77210
Country:US
Phone:800-231-6950
CAGE:54527

=====
===== Composition/Information on Ingredients =====

Ingred Name:HYDROTR
EATED MIDDLE PETROLEUM DISTILLATE
CAS:64742-46-7
RTECS #:JN9379645
Fraction by Wt: 20-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL
CAS:64742-53-6
RTECS #:PY8036000
Fraction by Wt: 20-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC
CAS:64742-56-9
RTECS #:PY8039500
Fraction by Wt: 35-40%
Other REC Limits:NONE RECOMMEN

DED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:CALCIUM HYDROXYSTEARATE
CAS:3159-62-4
Fraction by Wt: 10-12%
Other REC Limits:NONE RECOMMENDED

Ingred Name:OTHER COMPONENTS
Fraction by Wt: 300F,>149C
Spec Gravity:7.3
Evaporation Rate & Reference:UNKNOWN(BUTYL ACETATE=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:SMOOTH TAN GREASE, SLIGHT ODOR
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES
Hazardous Decomposition Products:A MIXTURE OF AIRBORNE SOLID, LIQUID PARTICULATES AND GASES (CO) WILL EVOLVE WHEN THIS MATERIAL UNDERGOES COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.