View NSN Online: https://aerobasegroup.com/nsn/8010-00-482-5652

Product ID:BOSTIK MSDS Date:01/01/1985 FSC:8010 NIIN:00-482-5652 Kit Part:Y MSDS Number: BDZYT === Responsible Party === Company Name: BOSTIK WEST, DIV. OF USM CORP, AN EMHART UNIT Emergency Phone Num:213-320-6800 CAGE:LO442 === Contractor Identification === Company Name: BOSTIK WEST, DIV. OF EMHART CORP CAGE:LO442 Company Name: MILITARY SPECIFICATIONS PROMULGATED BY MILITARY Address: DEPTS/AGENCIES UNDER AUTH OF DEF STD **Box:MANUAL** City:4120 3-M Phone:804-279-4371 DSN 695-4371 CAGE:81349

Ingred Name:ETHYL ACETATE RTECS #:KQ4900000 Fraction by Wt: 20-2% ACGIH TLV:400PPM

Ingred Name:CELLOSOLVE ACETATE RTECS #:FJ4375000 Fraction by Wt: 20-2% ACGIH TLV:100PPM

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS525

0000 Fraction by Wt: 15-2% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 5-10% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
======================================
Effects of Overexposure:HEADACHE,NAUSEA,DIZZINESS.BREATHING VAPOR WILL BE IRRITATING TO NOSE,THROAT AND EYES.
======================================
First Aid:SKIN EXPOSURE;WASH AFFECTED AREA WITH SOAP AND WATER.EYE EXPOSURE;FLUSH W/WATER FOR AT LEAST 15 MINUTES,CONSULT PHYSICIAN,INGESTION:CONSULT PHYSICIAN IMMEDIATELY.INHALATION:REMOVE VICTIM TO FRESH AIR, CONSULT PHYSICIAN.
======================================
Flash Point:24 F TCC -4C Lower Limits:1.0 Extinguishing Media:EXCLUDE AIR - USE FOAM,CO*2 STEAM,WATER FOG,DR Y CHEMICALS.DO
Fire Fighting Procedures:DO NOT USE WATER,EXCLUDE AIR,USE WATER SPRAY TO COOL FIRE EX Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER EXPLOSION LIMITS.
======================================

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION AND CLEAR FUMES FROM AREA.PREVENT LIQUID FROM ENTERING SEWERS, WATER SOURCES, OR LOW AREAS.KEEP UNNECESSARY PERSONNEL AWAY.SHUT OFF SOURCE, IF POS

SIBLE TO DO SO WITHOUT HAZA RD.CONTAIN SPILLED LIQUID W/SAWDUST OR OIL ABSORBI

Handling and Storage Precautions:MATERIAL IS SENSITIVE TO MOISTURE AND SHOULD BE KEPT IN TIGHTLY CLOSED CONTAINERS.
Other Precautions:ALL HANDLING EQUIPMENT SHOULD BE-ELECTRICALLY GROUNDED.TREAT AS A VERY FLAMMABLE LIQUID.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE APPROVED RESPIR ATORY PROTECTION SUCH AS AN AIR-SUPPLIED MASK IF Ventilation:FACE VELOSITY >60 FPM IN CONFINED AREA. Protective Gloves:CHEMICALLY RESI Eye Protection:CHEMICAL SPLASH GOGGLES O Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Supplemental Safety and Health 171-321 F 72-162 C

HCC:F3 Boiling Pt:B.P. Text:171-321 F Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:71%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS,INORGANIC ACIDS,SPARKS AND OPEN FIRE Stability Condition to Avoid:STORAGDE AT HIGH TEMPERATURES. Hazardous Decomposition Products:BY FIRE,CO,CO*2,OXIDES OF NITROGEN.AVOID CONTACT W/WATER,ALC

Waste Disposal Methods:USE APPROVED RESPIRATORY PROTECTION SUCH AS AN AIR-SUPPLIED MASK IF USED IN NON-VENTILATED

AREA.MECHANICAL:EXPLOSION-PROOF VENTILATION EQUIPMENT.NO SMOKING OR OPEN LIGHTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and ass

ume responsibility for the suitability of this information to their particular situation.