

DEFT, INC -- MIL-C-83286 -- 8010-00-482-5663

===== Product Identification =====

Product ID:MIL-C-83286
MSDS Date:01/01/1985
FSC:8010
NIIN:00-482-5663
MSDS Number: BDZZN
=== Responsible Party ===
Company Name:DEFT, INC
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92714-6205
Country:US
Info Phone Num:714-474-0400 / FAX 714-474-7269
Emergency Phone Num:714-474-0400
CAGE:5M511
=== Contractor
Identification ===
Company Name:DEFT, INC.
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92614
Country:US
Phone:949-474-0400
CAGE:33461
Company Name:DEFT, INC
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92714-6205
Country:US
Phone:714-474-0400
CAGE:5M511

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 10%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 P

PM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (SARA III)
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 10%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Fraction by Wt: 20%
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:MODERATE SKIN/E
YE IRRIT. INH: POSS NARCOSIS.

=====
First Aid Measures
=====

First Aid:SKIN: WIPE OFF W/RAG, RINSE, THEN WASH W/SOAP. EYE: FLUSH 10
MIN W/WATER & CONSULT MD. INH: REOVE TO FRESH AIR.

=====
Fire Fighting Measures
=====

Flash Point:28F, -2.2C OC
Lower Limits:1.6
Extinguishing Media:CO2, FOAM, DRY CHEM
Fire Fighting Procedures:DO NOT USE WATER STREAM, USE FOG NOZZ
Unusual Fire/Explosion Hazard:DO NOT APPLY TO HOT SURFAC
ES, AVOID
SPARKS/OPEN FLAMES

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB W/OIL-ABSORBING CMPD OR DRY RAGS. FLUSH
W/LG VOL WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN
FLAME
Other Precautions:AVOID PROLONGED INH OF VAPORS

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL EXHST FAN
Protective

Gloves:REQ
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:175-331F
Vapor Pres:15
Vapor Density:>AIR
Spec Gravity:1.2
Evaporation Rate & Reference: