View NSN Online: https://aerobasegroup.com/nsn/8010-00-482-5667
BOSTIK-FINCH, INC. -- BOSTIK -- 8010-00-482-5667

Product ID:BOSTIK MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5667

Kit Part:Y

MSDS Number: BDZZS === Responsible Party ===

Company Name: BOSTIK-FINCH, INC.

Address:434 W. MEAT ST.

City:ORANGE State:CA ZIP:92661 Country:US

CAGE:KO195

=== Contractor Identification ===

Company Name: AKZO COATINGS INC

Address:434 W. MEATS

STREET

Box:City:ORANGE

State:CA ZIP:92661 Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

Company Name: BOSTIK-FINCH, INC.

Address:434 W. MEAT ST.

Box:City:ORANGE

State:CA ZIP:92661 Country:US CAGE:KO195

======= Composition/Information on Ingredients ========

Ingred Name:SOLVENTS Fraction by Wt: 45.0% ACGIH TLV:100-400 PPM

Ingred Name: POLYESTER RESIN

Fraction by Wt: 19.1%

Ingred Name: ISOCYANATE PREPOLYMER (ALIPHATIC)

Fraction by Wt: 16.5%

Ingred Name:PIGMENTS

Fr

Ingred Name:ADDITIVES Fraction by Wt: 0.2%
========== Hazards Identification ===========
Effects of Overexposure:INHALE-IRRITATE NOSE & THROAT. MAY CAUSE NAUSEA OR VOMITING. MAY CAUSE EYE & SKIN IRRITATION.
======================================
First Aid:SKIN-WASH WITH SOAP & WATER. EYE-FLUSH WITH WATER; CONSULT DOCTOR. INHALE-REMOVE TO FRESH AIR;CONS;CONSULT DOCTOR.
========= Fire Fighting Measu
res ====================================
Flash Point:23F, -5C TCC Lower Limits:1.1
Extinguishing Media:CO2 OR DRY CHEM FOR SMALL; ALCOHOL FOAM FOR LARGE FIRES.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE.USE AIR SUPPLIED RESCUE EQUIPMENT.
Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTRICAL SPARKS MAY BE PRESENT
========= Accidental Release Measures =========
Spill Release Procedures: ABSORB WITH SAWDUST OR OIL ABSORBING COMPOUND.
WASH AREA WITH DETERGENT AND WATER. USE ADEQUATE VENTILATION TO CLEAR FUMES FROM AREA. AVOID SPARKS.
========== Handling and Storage ============
Handling and Storage Precautions:STORE UNDER 100F. KEEP AWAY FROM HEAT., SPARKS & OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE Other Precautions:DO NOT STOREOR MIX WITH STRONG OXIDANTS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:AIR SUPPLIED RESPIRATOR OR SUITA

action by Wt: 19.2%

Boiling Pt:B.P. Text:175-320F

Evaporation Rate & Dr. Reference:

Vapor Density:>AIR