

DEFT CHEMICAL COATINGS -- 03-GY-62 BASE,GREY 36622,POLYURETHANE -- 8010-00-482-5672

=====
Product Identification
=====

Product ID:03-GY-62 BASE,GREY 36622,POLYURETHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5672

Kit Part:Y

MSDS Number: BFBBG

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

CAGE:EO418

=== C

Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Effects of Overexposure:EYES:MODERATE IRRIT;SKIN:POSSIBLE IRRIT BY
SOLVENTS;INH:SOLVENT VAPORS

CAN CAUSE IRRIT OR NARCOSIS.

=====
===== First Aid Measures =====

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOUGH RINSING W/H*2O & WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE CPR.OXYGEN IF NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point:28F(-2.2C)-OC

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:W

EAR SELF-CNTND BRTHG APP:H*2O SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREASWHERE SOURCES OF IGNITION MAY BE PRESENT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG. SPILL:DIKE AHEAD FOR LATER DISPOSAL. NO TIFY AUTHORITIES.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID PROLONGED INHALATION OF VAPORS.IF VENTILATION IS POOR,USE A FRESH AIR SUPPLY MASK.DO NOT USE H*2O STREAM ON FIRE.H*2O SPRAY/FOG CAN BE USED EFFECTVLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SCBA,IN FIRE, OTHERWISE NIOSH APPRVD RESPIR Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATD:1/15/76;TWO PART PROD;THIS IS BASE;SEE P/N IND "B" FOR CATALYST;ALSO CONTAINS:0.8% TOLUENE,1.9% BARIUMSULFT,9.7 SILICA,0.3

%ANTI-SETLNG AGNT,0.4% DISPERSION AID (2)-NOW SEE ADDL
DATA.KEY1:F3

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:175-331F

Vapor Density:>1.0

Spec Gravity:1.2461

Evaporation Rate & Reference: