Address:17451 VON KARMAN AVE City:IRVINE State:CA

ZIP:92714-6205 Country:US CAGE:EO418

=== C

ontractor Identification ===

Company Name: DEFT CHEMICAL COATINGS

Company Name: DEFT CHEMICAL COATING

CAGE:EO418

Company Name: DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Country:US

Phone:949-474-0400

CAGE:33461

======= Composition/Information on Ingredients ========

Ingred Name: NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

========== Hazards Identification =============

Effects of Overexposure:EYES:MODERATE IRRITATION;SKIN:POSSIBLE IRRITATION BY SOLVENT;INH:SOLVE

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH RINSING W/H*20 & WASHING W/MILD SOAP AND WATER:EYES:FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE CPR/OXY IF NEEDED.	NT VAP CAN CAUSE IRRIT/NORCOS.
WASHING W/MILD SOAP AND WATER; EYES; FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN; INH: REMOVE TO FRESH AIR. GIVE CPR/OXY IF NEEDED. ================================	======================================
Flash Point:28F(-2.2C)-OC Lower Limits:UNK Upper Limits:UNK Upper Limits:UNK Extinguishing Media:CARBON DIOXIDE,FOAM OR DR Y CHEMICALS. Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP;CAN USE H*2O SPRAY/FOG EFFECTIVLY. Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT. ===================================	WASHING W/MILD SOAP AND WATER; EYES: FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN; INH: REMOVE TO FRESH AIR. GIVE CPR/OXY
Lower Limits:UNK Upper Limits:UNK Extinguishing Media:CARBON DIOXIDE,FOAM OR DR Y CHEMICALS. Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP;CAN USE H*20 SPRAY/FOG EFFECTIVLY. Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT. ===================================	======================================
Y CHEMICALS. Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP;CAN USE H*20 SPRAY/FOG EFFECTIVLY. Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT. ===================================	Lower Limits:UNK
Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP;CAN USE H*20 SPRAY/FOG EFFECTIVLY. Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT. ===================================	
SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT.	Fire Fighting Procedures: USE SELF-CNTND BRTHNG APP; CAN USE H*20
Spill Release Procedures:EVACUATE UNPROTED PERSONS.ELIM IGN SOURCES;PROVIDE VENT & SAFETY EQUIPMENT.STOP LEAK W/O RISK;ABSORB SM SPILL SPILL W/OIL ABSORBNG COMPD OR RAGS.PER MFR,FLUSH AREA W/LG AMT H*2O;DIKE LG SPILL.PUMP LIQ INTO SALVGE TANK & SHOVEL UP RESIDUE IN CNTNR ==================================	· ·
SOURCES;PROVIDE VENT & SAFETY EQUIPMENT.STOP LEAK W/O RISK;ABSORB SM SPILL SPILL W/OIL ABSORBNG COMPD OR RAGS.PER MFR,FLUSH AREA W/LG AMT H*2O;DIKE LG SPILL.PUMP LIQ INTO SALVGE TANK & SHOVEL UP RESIDUE IN CNTNR	======== Accidental Release Measures =========
AMT H*2O;DIKE LG SPILL.PUMP LIQ INTO SALVGE TANK & SHOVEL UP RESIDUE IN CNTNR ==================================	SOURCES;PROVIDE VENT & SAFETY EQUIPMENT.STOP LEAK W/O RISK;ABSORB SM SPILL SPILL W/OIL ABSORBNG COMPD OR RAGS.PER MFR,FLUSH
Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTCT FROM PHYSICAL DAMAGE. Other Precautions:AVOID PROLONGED INHALATION OF VAPORS.IF VENTILATION IS POOR,A FRESH AIR SUPPLY MASK IS RECOMMENDED.AVOID PHYSICAL CONTACT.	AMT H*2O;DIKE LG SPILL.PUMP LIQ INTO SALVGE TANK & SHOVEL UP
FIRE RISK AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTCT FROM PHYSICAL DAMAGE. Other Precautions:AVOID PROLONGED INHALATION OF VAPORS.IF VENTILATION IS POOR,A FRESH AIR SUPPLY MASK IS RECOMMENDED.AVOID PHYSICAL CONTACT.	======================================
IS POOR,A FRESH AIR SUPPLY MASK IS RECOMMENDED.AVOID PHYSICAL CONTACT.	FIRE RISK AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTCT FROM PHYSICAL
====== Exposure Controls	IS POOR,A FRESH AIR SUPPLY MASK IS RECOMMENDED.AVOID PHYSICAL
	====== Exposure Controls

/Personal Protection =======

Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR PAINT,LAQUER,ENAMEL & ORGAIC VAPOR.

Ventilation: ADEQUATE USING EXHAUST FAN.

Protective Gloves: NEOPRENE/RUBBER

Eye Protection: SAFETY/CHEM GOGGLE W/SHLD

Other Protective Equipment: USE CARTRIDGE TYPE RESPIRATOR W/PARTICULATE FILTERS.

Supplemental Safety and Health

MSDS FM MFR DATES:1/15/76;TWO PART KIT:COMPONENT I(BASE) & COMPONENT II(CATALYST);TYPE 1 MATL OF MIL-C-83286B;THIS IS CATALYST.KEY1:F3

======== Physical/Chemical Properties ==========

HCC:F3

Boiling Pt:B.P. Text:175-331F

Vapor Density:>1.0 Spec Gravity:0.9131

Evaporation Rate & Deference: