

BOSTIK-FINCH, INC. -- BOSTIK -- 8010-00-482-5672

=====
Product Identification
=====

Product ID:BOSTIK

MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5672

Kit Part:Y

MSDS Number: BFBBJ

=== Responsible Party ===

Company Name:BOSTIK-FINCH, INC.

Address:434 W. MEAT ST.

City:ORANGE

State:CA

ZIP:92661

Country:US

CAGE:KO195

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS

STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

Company Name:BOSTIK-FINCH, INC.

Address:434 W. MEAT ST.

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

CAGE:KO195

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 45.0%

ACGIH TLV:100-400 PPM

Ingred Name:POLYESTER RESIN

Fraction by Wt: 19.1%

Ingred Name:ISOCYANATE PREPOLYMER (ALIPHATIC)

Fraction by Wt: 16.5%

Ingred Name:PIGMENTS

Fr

action by Wt: 19.2%

Ingred Name:ADDITIVES

Fraction by Wt: 0.2%

=====
Hazards Identification
=====

Effects of Overexposure:INHALE-IRRITATE NOSE & THROAT. MAY CAUXE NAUSEA OR VOMITING. MAY CAUSE EYE & SEEKING IRRITATION.

=====
First Aid Measures
=====

First Aid:SKIN-WASH WITH SOAP & WATER. EYE FLUSH WITH WATER. EYE FLUSH WITH WATER; CONSULT DOCTOR. INHALE-REMOVE TO FRESH AIR;CONSULT DOCTOR. INGESTION. INDUCE VOMITING; CONSULT DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point:23F, -5C TCC

Lower Limits:1.1

Extinguishing Media:CO2 OR DRY CHEM FOR SMALL;ALCOHOL FOAM FOR LARGE FIRES.

Fire Fighting Procedures:WTER MAY BE INEFFECTIVE.USE AIR SUPPLIED RESCUE EQUIPMENT.

Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTRICAL SPARKS MAY BE PRESENT.

=====
Accidental Release Measures
=====

Spill

Release Procedures:ABSORB WITH WAWDUST OR OIL ABSORBING COMPOUND. WASH AREA WITH DETERGENT AND WATER. USE ADEQUATE VENTILATION TO CLEAR FUMES FROM AREA. AVOID SPARKS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE UNDER 100F. KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NORT IN USE.

Other Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

=====
Exposure Controls/Personal Protection
=====

=====

Respiratory Protection: AIR SUPPLIED RESPIRATOR OR SUITABLE CHEMICAL CARTRIDGE.

Ventilation: TO MEET TLV

Protective Gloves: SOLVENT RESISTANT

Eye Protection: GOGGLES OR FACE SHIELD

Other Protective Equipment: COVERALLS, APRON, NON-SPARKING SAFETY SHOES, ETC.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 175-320F

Vapor Density: > AIR

Evaporation Rate & Reference: ETHER

Percent Volatiles by Volume: 5

7.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS

Hazardous Decomposition Products: CO & COMBUSTION PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE WITH CARE SANITARY LAND FILL PREFERABLE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The

United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.