

SHORE-UBS CHEMICAL COMPANY -- N-1030 -- 8040-00-515-2246

=====
Product Identification
=====

Product ID:N-1030
MSDS Date:01/01/1987
FSC:8040
NIIN:00-515-2246
Kit Part:Y
MSDS Number: BFCDB
=== Responsible Party ===
Company Name:SHORE-UBS CHEMICAL COMPANY
Address:100 MAIN ST
City:ALLENHURST
State:NJ
ZIP:07711-1131
Country:US
CAGE:31711
=== Contractor Identification ===
Company Name:SHORE-UBS CHEMICAL
CO INC
Address:100 MAIN ST
Box:City:ALLENHURST
State:NJ
ZIP:07711-1131
Country:US
Phone:201-531-7300
CAGE:31711

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS
Fraction by Wt: 72.0%
ACGIH TLV:350 PPM

Ingred Name:VEHICLE
Fraction by Wt: 17.0%

=====
Hazards Identification
=====

Effects of Overexposure:NARCOSIS, STUPOR, DROWSINESS

=====
First Aid Measures
=====

First Aid:FRESH

AIR AND/OR OXYGEN. OBTAIN MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:20 F,-6.7 C TOC

Lower Limits:1.2

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, POWDER CHEMICALS, TRICHLORETHANE

Fire Fighting Procedures:NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:AVOID CONTACT WITH OXIDIZERS, OPEN FLAMES, SPARKS, AND HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:APPLY DRI-RITE OR SPEED-DRY ABSORBENT MATERIALS TO SOAL UP LIQUID.

=====
Handling and Storage
=====

Handling and Storage Precautions:REASONABLE CAUTION TO AVOID CONTACT WITH SKIN. STORE IN FLAMMABLE STORAGE AREA AT 60-90 F.

Other Precautions:KEEP OUT OF DIRECT SUNLIGHT. KEEP IN SEALED CONTAINERS.

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL-PREVENT VAPOR BUILD-UP. MECHANICAL-CROSS VENTILATION.

Protective Gloves:YES

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:202 F; 94 C

Vapor Pres:100

Vapor Density:3.06

Spec Gravity:0.875

Evaporation Rate & Reference:2.9 BUAC

Solubility in Water:NA

Appearance and Odor:OPAQUE, CREAM COLOR; MOTHBALL, RUBBERY ODOR

Percent Volatiles by Volume:81

=====
Stability and Reactivity Data
=====

Stabilit

y Indicator/Materials to Avoid: YES

OXIDES OF C, S, N, ZN, MG AND C1. FORMALDEHYDE AND AMMONIA.

Stability Condition to Avoid: OXIDIZERS, OPEN FLAME, SPARKS AND HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods: SOLVENT WASTE STEEL DRUM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.