

ATLAS PAINT & VARNISH CO. -- TT-E-435 TYPE II -- 8010-00-526-1609

=====
Product Identification
=====

Product ID:TT-E-435 TYPE II

MSDS Date:01/01/1987

FSC:8010

NIIN:00-526-1609

MSDS Number: BFCMM

=== Responsible Party ===

Company Name:ATLAS PAINT & VARNISH CO.

Emergency Phone Num:201-373-3300

CAGE:KO008

=== Contractor Identification ===

Company Name:ATLAS PAINT & VARNISH CO.

CAGE:KO008

Company Name

e:ATLAS PAINT AND VARNISH CO

CAGE:84239

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD COBALT DRIERS (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt: 1%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:ALKYD RESIN

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB29750

00

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR 1910.1025)

CAS:1314-41-6

RTECS #:OG5425000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION OF HIGH CONCENTRA. W/O PROPER VENT.
MAY CAUSE MILD DEPRESSION & LOSS OF CONSCIOUSNESS.

=====
First Aid Measures
=====

First Aid:REM

OVE FROM EXPOSURE-CALL PHYSICIAN, FLUSH AFFECTED PARTS WITH WATER.

===== Fire Fighting Measures =====

Flash Point:108F TCC
Lower Limits:0.09
Upper Limits:6.0
Extinguishing Media:CO2-FOAM-DRY CHEMICAL-WATER FOG
Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT-COOL EXPOSED CONTAINERS

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY AND DISCARD ABSORBENTS SAFELY. REMOVE OPEN I
GNITION. DIKE LARGE SPILLS AND PUMP INTO WASTE TANK. KEEP VENTILATED AND AVOID PROLONGED BREATHING OF VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES- SPARKS AND EXCESSIVE HEAT - VENTILATE AREA
Other Precautions:READ LABEL REGARDING TOXICITY AND APPLICATION.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST MOST DESIRABLE
Protective Gloves:RECOMMEND
Eye Protectio
n:RECOMMEND
Other Protective Equipment:CONVENTIONAL CLOTHES FOR PAINTING
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:317-388F
Vapor Density:4.8
Evaporation Rate & Reference:SLOWER THAN BUTYL
Solubility in Water:NEGATIVE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXYGEN AND STRONG OXIDENTS
Stability Condition to Avoid:OPEN FLAME
Hazardous

Decomposition Products:CO AND CO2 WHEN COMBUSTED

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.