

J.LANDAU & CO.,INC,214 WASHINGTON AV,CARSTADT,NJ -- NITROCELLULOSE LACQUER-WHITE  
17875 -- 8010-00-527-2493

=====  
Product Identification  
=====

Product ID:NITROCELLULOSE LACQUER-WHITE 17875

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2493

MSDS Number: BFCSR

==== Responsible Party ====

Company Name:J.LANDAU & CO.,INC,214 WASHINGTON AV,CARSTADT,NJ

Emergency Phone Num:201-939-7418

CAGE:LO520

==== Contracto

r Identification ===

Company Name:J.LANDAU & CO.,INC,214 WASHINGTON AV,CARSTADT,NJ

CAGE:LO520

Company Name:LANDAU J AND CO INC

Address:214 WASHINGTON AVE

Box:City:CARLSTADT

State:NJ

ZIP:07072-2902

Country:US

Phone:201-939-7418

CAGE:98068

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 16.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LB

S

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 17.0%

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 3.0%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

M; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC,IRRITATION OF THE RESPIRATORY TRACT  
OR ACUTE NERVOUS SYSTEM;HEADACHE,DIZZINESS,COMA

===== First Aid Measures =====

First Aid:FUMES:REMOVE FROM EXPOSURE,RESTORE BREATHING,KEEP WARM AND  
QUIET,NOTIFY A PHYSICIAN.EYES:FLUSH IMMEDIATELY WITH COPIOUS AMOUNT  
OF WATER FOR 15 MIN.SKIN:REMOVE WITH SOAP AND WATER.REMOVE  
CONTAMINATED CLOTHING. CALL PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:22F TOC  
Extinguishing Media:WATER SPRAY,FOAM,CO2,DRY CHEMICAL  
Fire Fighting Procedures:WATER SPRAY TO COOL DOWN CLOSED CONTAINERS  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE  
FROM HEAT,ELECTRICAL EQUIP,SPARKS AND OPEN FLAME

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OR  
CONTAINER.AVOID EXPOSURE TO SPARKS,OPEN FLAME,ETC

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION.KEEP  
AWAY FROM HEAT,SPARKS,AND OPEN FLAME.AVOID PROLONGED OR REPEATED  
CONTACT WITH THE SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS FOR  
CONCENTRATIONS ABOVE TLV VALUE  
Ventilation:LO

CAL EXHAUST PREFERRED AND RECOMMENDED.

Protective Gloves:SOLVENT RESIS.

Eye Protection:FACE SHIELD OR MASK

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO HOT SURFACES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:176-241F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:73

=====

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT,SPARKS,OPEN FLAME,ETC

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF IN ACCORDANCE WITH CITY SATE AND,FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.