

PRATT AND LAMBERT INC -- 745412 ENAMEL ALKYD SG GREEN 24148 -- 8010-00-527-2628

=====
Product Identification
=====

Product ID:745412 ENAMEL ALKYD SG GREEN 24148

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2628

MSDS Number: BFCVS

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergen

cy Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 35%

ACGIH TLV:500 PPM

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

=====

=====
Hazards Identification
=====

Effects of Overexposure: INHAL: ANEST IRRITATION OF RESPIRATORY TRACT OR ACUT NERV SYS DEPRSSN, HDACH, DIZZ, CONFUSN, UNCON, COMA.

=====
First Aid Measures
=====

First Aid: IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A DR IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point: 104F TCC 40C

Extinguishing Media: CO₂, DRY CHEM OR ALCOHOL FOAM. POLYMER FOAM RECOMMENDED FOR FLAMING LIQUID FIRES

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS WATER SPRAY MAY BE INEFFECTIVE

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE (SUPPORT)

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATISTICAL, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BLDG DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions: CONTAINERS SHOULD BE GROUND WHEN POURING. AVOID FREE FALLOUT OF LIQUID IN EXCESS OF FEW INCHES. DO NOT FLAME CUT, BRAZE, WELD COATED MATERIAL WITHOUT APPROPRIATE RESPIRATORY OR APPROPRIATE VENTILATION. ADVISE WARNING LABELS - DO NOT TAKE INTERNALLY

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: MECHANICAL FILTER RESPIRATOR OR REMOVE SOLID BORNE PARTICLES/OVERSPRAY INDOR.

Ventilation: LOCAL EXHAUST VENTILATION TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS

Protective Gloves: F/PRLNG/REPEAT

Eye Protection: SAFETY EYEWEAR PROTECT AGAINST

Other Protective Equipment: PREVENT Prolonged Skin Contact to Contaminated Clothing.

Supplemental Safety and Health

UNUS. FIRE/EXPLOS. HAZARDS: WHEN EXPOSED

XPOSED TO EXTREME HEAT. DO NOT APPLY TO
VERY HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRES, HEAT, & HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL
REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.