

EASTMAN KODAK COMPANY -- 146 4114, KODAK RAPID FIXER, PART B -- 6750-00-528-0473

=====
Product Identification
=====

Product ID:146 4114, KODAK RAPID FIXER, PART B

MSDS Date:11/08/1995

FSC:6750

NIIN:00-528-0473

Kit Part:Y

MSDS Number: BFCYR

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194

MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====
Composition/Information on Ingredient

S =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 70-75%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM SULFATE
CAS:10043-01-3
RTECS #:BD1700000
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SULFURIC ACID (SARA 302/313) (CERCLA)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/
M3/3 STEL; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): 0.5-5.0 G/KG
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION-EXPECTED TO BE A LOW
INHALATION HAZARD FOR RECOMMENDED HANDLING. EYE-CAUSES IRRITATION.
SKIN-CAUSES IRRITATION. INGESTION-HARMFUL IF SWALLOWED. MAY CAUSE
BURNS
OF THE GASTROINTESTINAL TRACT IF SWALLOWED.
Explanation of Carcinogenicity:IARC HAS DETERMINED THAT OCCUPATIONAL
EXPOSURE TO STRONG ACIDS MAY BE CARCINOGENIC TO HUMANS.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL
ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WI

TH WATER

FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: IMMEDIATELY REMOVE CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:MAY REQUIRE NEUTRALIZATION. FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLES.

Other Precautions:DO NOT BREATHE MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER. WEAR PROTECTIVE CLOTHING APPROPRIATE FOR THE RISK OF EXPOSURE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

KEY1;C1.REFER TO PNIND-D(PT.A);PNIND-W(W

WORKING SOLUTION FOR
FILM);PNIND-X(WORKING SOLUTION FOR PAPER).

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:>100.C, 212.F

Vapor Pres:18 MMHG

Vapor Density:0.6

Spec Gravity:1.30

pH:1.0

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, SLIGHT SULFUR DIOXIDE ODOR

Percent Volatiles by Volume:70-75%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES

Stability Condition

to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT
TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH
< 2.0 OR PH > 12.5. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the
Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.