

EASTMAN KODAK COMPANY -- 190 0703 FLEXICOLOR STABILIZER/REPLENISHER, --  
6750-00-539-9540

=====  
===== Product Identification =====

Product ID:190 0703 FLEXICOLOR STABILIZER/REPLENISHER,

MSDS Date:12/15/1990

FSC:6750

NIIN:00-539-9540

Kit Part:Y

MSDS Number: BFDKX

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone N

um:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====  
===== Composition/Information on Ingredients =

=====

Ingred Name:FORMALDEHYDE (SARA III)  
CAS:50-00-0  
RTECS #:LP8925000  
Fraction by Wt: 10-15%  
OSHA PEL:SEE 1910.1048  
ACGIH TLV:C 0.3 PPM; A2; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)  
CAS:67-56-1  
RTECS #:PC1400000  
Fraction by Wt: 1-5%  
Other REC Limits:ACGIH STEL 250 PPM  
OSHA PEL:S,200PPM/250STEL  
ACGIH TLV:S,200PPM/250STEL; 93  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:WATER (85-90%)  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction  
by Wt: 85-90%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:INHALATION: MAY CAUSE RESPIRATORY SENSITIZATION IN SOME INDIVIDUALS. EYES: CAUSES EYE IRRITATION AND TEARING. CONTACT WITH THE LIQUID CAN CAUSE SEVERE EYE BURNS. SKIN: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC REACTION. INGESTION: POISON! MAY BE FATAL OR CAUSE BLINDNESS. CAUSES BURNS TO CONTACTED AREAS.  
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS FORMALDEHYDE.  
Effects of Overexposure:INGESTING THIS MATERIAL CAUSES IMMEDIATE SEVERE ABDOMINAL PAIN WITH VOMITING, NAUSEA, DIARRHEA, DIZZINESS, UNCONSCIOUSNESS OR COMA, ANURIA, CONVULSIONS, AND POSSIBLE DEATH.  
Medical Cond Aggravated by Exposure:MAY AGGRAVATE PRE-EXISTING ASTHMATIC CONDITIONS.

===== First Aid Measures =====

Firs

t Aid:INHALATION: REMOVE TO FRESH AIR. ASSIST WITH BREATHING IF NECESSARY. EYES AND SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN. AND GET MEDICAL ATTENTION, IF NEEDED. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, IMMEDIATELY GIVE VICTIM ONE GLASS OF WATER. CALL A POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.

Fire

Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN VERMICULITE OR OTHER SUITABLE ABSORBENT AND PLACE IN IMPERVIOUS CONTAINER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Stor

age Precautions:NONE

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF NECESSARY, A FULL FACEPIECE WITH CARTRIDGES OR CANISTERS SPECIFICALLY APPROVED BY NIOSH FOR PROTECTION AGAINST FORMALDEHYDE OR A TYPE 'C' SUPPLIED AIR RESPIRATOR.

Ventilation:LOCAL EXHAUST VENTILATION OR AN ENCLOSED HANDLING SYSTEM MAY BE NEEDED TO CONTRIL AIR CONTAMINATION.

Protective Gloves:NITRILE OR NEOPRENE GLOVES

Eye Protection:GOGGLES AND FACE SHIELDS

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:THE ROUTINE USE OF A NON-ALKALINE TYPE OF SKIN CLEANSER AND REGULAR CLEANING OF WORKING SURFACES, GLOVES, ETC.

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 MM HG

Vapor Density:0.6

Spec Gravity:1.02

pH:3.5

Evaporation Rate & Reference:0.4 (N-BUTYL ACETATE=1)

Solubility in Water:CO

MPLETE

Appearance and Odor: CLEAR, COLORLESS SOLUTION WITH AN ALDEHYDE ODOR.

Percent Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid: HIGH TEMPERATURES. FORMALDEHYDE GAS MAY EVOLVE.

Hazardous Decomposition Products: FORMALDEHYDE GAS MAY BE EVOLVED.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE BY INCINERATION OR CONTRACT WITH A LICENSED CHEMICAL WASTE DISPOSAL AGENCY. DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.