DOW CORNING CORP -- DOW CORNING 200 FLUID, 20 CST -- 9150-00-543-7219

Product ID:DOW CORNING 200 FLUID, 20 CST MSDS Date:04/16/1990 FSC:9150 NIIN:00-543-7219 **MSDS Number: BFDPS** === Responsible Party === Company Name: DOW CORNING CORP Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAND State:MI ZIP:48640 Country:US Info Phone Num:517-496-6000 **Emergency Phone Num:** 517-496-5900 Preparer's Name: JACK L. SHENEBERGER CAGE:5D028 === Contractor Identification === Company Name: ACCUMETRIC INC Address:350 RING RD Box:843 City:ELIZABETHTOWN State:KY ZIP:42701 Country:US Phone:502-769-3385 CAGE:58149 Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496

-4388 CAGE:71984 Company Name: R.H.CARLSON COMPANY, INC. Address:41-CHESTNUT STREET Box:1687 City:GREENWICH State:CT ZIP:06830-5921 Country:US Phone:203-531-5500 CAGE:33530 Ingred Name: DIMETHYL POLYSILOXANE (DOW CORNING 200) CAS:63148-62-9 RTECS #:JT6484500 Fraction by Wt: >98.0% Other REC Limits:NONE SPECIFIED Routes of Entry: Inhalation:NO Skin:NO Ingesti on:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE EFFECTS: TEMPORARY EYE IRRITATION AND DRYNESS, CHRONIC EFFECTS:NONE KNOWN. Explanation of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects of Overexposure: EYES: MILD REDNESS, DRYNESS. SKIN: SINGLE PROLONGED EXPOSURE CAUSES NO ADVERSE EFFECTS. INHALATION:NO INJURY IS LIKELY. INGESTION: SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTI VE DISCOMFORT. Medical Cond Aggravated by Exposure:NONE KNOWN. First Aid: EYES: FLUSH IMMEDIATELY WITH PLENTY OF WATER. SKIN: WIPE OFF AND FLUSH WITH PLENTY OF WATER. INHALATION:NO FIRST AID SHOULD BE NEEDED. INGESTION:NO FIRST AID SHOULD BE NEEDED.

Flash Point Method:OC Flash Point:400F,204C Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM

, OR DRY CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.
======================================
Spill Release Procedures:ABSORB IN INERT MATERIAL AND PLACE IN APPROPIATE DISPOSAL CONTAINER A ND COVER.
======================================
 Handling and Storage Precautions:STORE AT ROOM TEMPERATURE.KEEP CONTAINER CLOSED WHEN NOT IN USE Other Precautions:PRECAUTIONS STATED ARE FOR PRODUCT AT ROOM TEMPERATURE.ADDED PRECAUTIONS SHOULD BE TAKEN AT ELEVATED TEMPERATURES.TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED IN AIR ABOVE 300F (149C).PROVID E VENTILATION.
======================================
Res
piratory Protection:NONE NORMALLY REQUIRED WITH ADEQUATE VENTILATION.
Ventilation:MECHANICAL (GENERAL) VENTILATION RECOMMENDED TO KEEP EXPOSURE BELOW PEL.
Protective Gloves: RUBBER GLOVES.
Eye Protection:SAFETY GLASSES. Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety a
nd Health PRODUCT IS SENSITIVE TO CONTAMINATION AT ELEVATED TEMPERATURES. FLASH POINT AND VISCOSITY MAY CHANGE IF CONTAMINATED BY STRONG ACIDS, BASES, SOME METALLIC COMPOUNDS AND OXIDIZING AGENTS.
======================================

HCC:V6 Boiling Pt:B.P. Text:300F/149C Vapor Pres: