View NSN Online: https://aerobasegroup.com/nsn/6810-00-546-4343

E.I. DUPONT DE NEMOURS & CO,INC -- FREON T-P 35 -- 6810-00-546-4343

Product ID: FREON T-P 35 MSDS Date:01/01/1985 FSC:6810 NIIN:00-546-4343 **MSDS Number: BFDTM** === Responsible Party === Company Name: E.I. DUPONT DE NEMOURS & CO, INC Address:1007 MARKET STREET Box:1635 City:WILMINGTON State:DE ZIP:19899 Country:US Info Phone Num:800-441-7515 **Emergency Phone Num:800-4** 41-7515 CAGE:19898 === Contractor Identification === Company Name: E.I. DUPONT DE NEMOURS & CO Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:800-441-7515;800-441-9442 CAGE:18873 Company Name: E.I. DUPONT DE NEMOURS & CO., INC. Box:1635 CAGE:19898

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 64.7% OSHA PEL:1000PPM/ 1250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1

Ingred Name:NITROMETHANE CAS:75-52-5 RTECS #:PA9800000 Fraction by Wt: 0.3% OSHA PEL:100 PPM ACGIH TLV:100 PPM; 9192

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 35% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Effects of Overexposure:LIGHT-HEAD,GIDDY,SHORT OF BRTH,POSSIBL NARCOSIS,POSSIBLE CARDIAC A RRHYTHMIAS AT HIGH CONCENTRATIONS.

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET.DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS.

Flash Point:120F/49C TOC Lower Limits:UNK Upper Limits:UNK Extinguishing Media:ANY AVAILABLE TYPE RECOMMENDED BY MFR. Fire Fighting Proced ures:WEAR SELF-CNTND BRTHG APP,IF INVOLVED IN FIRE. Unusual Fire/Explosion Hazard:ADDITION OF EXCESS WATER(>9%) WILL EXTRACT ALCOHOL AND MAY FORM A FLAMMABLE,SUPERNATANT LIQUID LAYR.

Spill Release Procedures: VENTILATE AREA.ELIMINATE IGNITION SOURCES, ESPECIALLY LOW AREAS WHERE VAPORS MIGHT COLLECT.STOP LEAK.WEAR PROTECTIVE CLOTHES, SCBA.ABSORB SM SPILL WITH SUITABLE ABSORBENT.SHOVEL INTO CONTAINER.LG SPILL: DIKE

## WITH SUITABLE ABSORBENT FOR LATER DISPOSAL.

Handling and Storage Precautions:STORE IN CLEAN, DRY, WELL VENTED AREA.KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL DAMAGE.DO NOT STROE ABOVE 125F.

Other Precautions:FOR FURTHER INFORMATION,SEE FREON PRODUCTS BULLETIN S-16,FST-5F,S-30.

======= Exposure Controls/Personal Protection ==========

Ventilation: MECHAN. IN LOW PLACES; LOCAL EXHAUST WHEN LARGE AMTS

RELEASED Protective Gloves:IMPERVIOUS Eye Protection:CHEM SPLASH GOGGLES Other Protective Equipment:USE APPROPEATE HYGIENE PRACTICES. Supplemental Safety and Health FLASH POINT DECREASES AFTER 40% EVAPORATES.MIST/SPRAY IS FLAMMABLE.

HCC:F4 Boiling Pt:B.P. Text:120F/49C Vapor Pres:284 Vapor Density:2.2 Spec Gravity:1.15 Evaporation Rate & amp; Reference:3.7(CARBON TET=1) Solubility in Water:MODERATE Appearance and Odor:COLORL ESS LIQUID-SLIGHT SOLVENT ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ALKALI OR ALKALINE EARTH METALS-POWDERED AL,ZN,BE,ETC. Stability Condition to Avoid:HIGH TEMPERATURES,IGNITION SOURCES Hazardous Decomposition Products:HYDROCHLORIC AND HYDROFLUORIC ACIDS-POSSIBLE PHOSGENE.

Waste Disposal Methods: ELIMINATE IGNITION

SOURCES.CONTACT QUALIFIED

DISPOSAL CONTRACTOR OR MANUFACTURER FOR DISPOSAL METHODS.SEND TO MFR/DISPOSAL CONTRACTOR FOR RECYLE BY DISTILLATION.PACKAGE & DISPOSE IN ACCORDANCE WITH LO CAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurat e and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.