

LOCTITE CORP -- FORM-AGASKET #2, MIL-S-45180B, TYPE II

=====
MSDS Safety Information
=====

FSC: 8030
NIIN: 00-551-1059
MSDS Date: 09/13/1993
MSDS Num: BFDYS
Product ID: FORM-AGASKET #2, MIL-S-45180B, TYPE II
MFN: 01
Responsible Party
Cage: 7K128
Name: LOCTITE CORP
Address: 705 N MOUNTAIN ROAD
City: NEWINGTON
CT 06111
Info Phone Number: 203-278-1280
Emergency Phone Number: 203-278-1280
Preparer's Name: STEPHEN REPETTO
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 7K128
Name: LOCTITE CORP
Address: 705 N MT RD
City: NEWINGTON CT 06111
Phone: 312-689-6200
Cage: 08028
Name: LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP
Address: 4450 CRANWOOD COURT
City: CLEVELAND OH 44128-4004
Phone:
216-663-3011

=====
Item Description Information
=====

Item Manager: GSA
Item Name: SEALING COMPOUND
Unit of Issue: TU
Quantitative Expression: 00000000003OZ
UI Container Qty: 0
Type of Container: TUBE

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

Signs And Symptoms Of Overexposure: CAN ACT AS LOCAL IRRIT. MFR STATES PROD NOT CONSIDERED IMPORTANT TOXIC HAZ.

First Aid: SKIN: WASH THOROUGHLY W/MILD SOAP & WATER AFTER HANDLING. EYES: IMMED FLUSH W/WATER AT LEAST 15 MIN, CALL MD.
=====

Handling and Disposal
=====

Spill R

Release Procedures: MFR SUGGESTS CLEANING UP W/ISOPROPANOL TAKING PRECAUTIONS AGAINST POSS FIRE & INH HAZ.

Waste Disposal Methods: SM AMTS: HANDLE AS COMBUSTIBLE. LG AMTS: SANITARY LANDFILL, MFR SUGGESTIONS. DISPOSE IAW LOCAL, STATE, FED REG.

Handling And Storage Precautions: STORE IN COOL, DRY PLACE NOT OVER 120F

Other Precautions: BP, VAP PRESS & EVAP RATE GIVEN FOR SLVNT. MFR CODE: PART #2. PROD INSOLUBLE IN WATER WHEN DRIED. VAP PRESS: 31.2MMHG.
=====

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 69.0F,20.6C

Lower Limits: 2%

Upper Limits: 12%

Extinguishing Media: CO*2, DRY CHEMICAL, FOAM

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE
=====

Control Measures
=====

Respiratory Protection: NOT REQ

Ventilation: LOCAL EXHST ADEQUATE

Protective Gloves: NOT REQ

Eye Protection: NOT REQ
=====

Physical/Chemical Properties
=====

B.P. Text: 180F,82C

Vapor Pres: 35 @ 68F

Vapor Density: 2.07

Spec Gravity: 1.50

Evaporation Rate & Reference: 7.7 (ETHER=1)

Solubility in Water: PARTIAL

Appearance and Odor: BLACK PASTE, ALCOHOLIC ODOR
=====

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: STRONG OXIDIZERS.

Hazardous Polymerization Indicator: NO

=====

Toxicological Information

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

Regulatory Information

=====

=====

Other Information

=====

=====

=====

Transportation Information

=====

Responsible Party Code: 7K128

Trans ID NO: 76423

Product ID: FORM-AGASKET #2, MIL-S-45180B, TYPE II

MSDS Prepared Date: 09/13/1993

Review Date: 06/14/1995

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: TU

Container QTY: 0

Type Of Container: TUBE

Additional Data: NOT REGULATED FOR SHIPPING

=====

Detail DOT Information

=====

=====
DOT PSN Code: GKA
DOT Proper Shipping Name: FLAMMABLE SOLIDS, N.O.S
Hazard Class: 4.1
UN ID Num: UN1325
DOT Packaging Group: III
Label: FLAMMABLE SOLID
Packaging Exception: 151
Non Bulk Pack: 213
Bulk Pack: 240
Max Qty Pass: 25 KG
Max Qty Cargo: 100 KG
Vessel Stow Req: B
=====

=====
Detail IMO Information
=====

IMO PSN Code: HJB
IMO Proper Shipping Name: FLAMMABLE SOLID
, ORGANIC, N.O.S. o
IMDG Page Number: 4146
UN Number: 1325
UN Hazard Class: 4.1
IMO Packaging Group: II/III
Subsidiary Risk Label: -
EMS Number: 4.1-05
MED First Aid Guide NUM: T
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

=====
AFI PSN DL
AFI Symbols: *
AFI Proper Shipping Name: FLAMMABLE SOLIDS, INORGANIC, N.O.S.
AFI Hazard Class: 4.1
AFI UN ID NUM: UN1378
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A8.4
=====

=====
HAZCOM Label
=====

Product ID: FORM-AGASKET #2, MIL-S-45180B, TYPE II
Cage: 7K128
Company Name: LOCTITE CORP
Street: 705 N MT RD
City: NEWINGTON C

T

Zipcode: 06111

Health Emergency Phone: 203-278-1280

Label Required IND: Y

Date Of Label Review: 05/03/1994

Status Code: C

Label Date: 05/03/1994

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: STORE AWAY FROM HEAT AND FLAME. AVOID EYE AND SKIN CONTACT. ACUTE: MODERATELY TOXIC BY INGESTION. VAPOR ABOVE TLV I

S IRRITATING

TO EYES, NOSE AND THROAT AND CAN CAUSE HEADACHE, DIZZINESS AND NAUSEA. EYE IRRITANT. CHRONIC: NONE LISTED BY MANUFACTURER.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regard

less of similarity to a corresponding Department of Defense or other government situation.