FSC:6810

NIIN:00-551-1487

MSDS Number: BFDZD === Responsible Party ===

Company Name:BRULIN & COMPANY, INC. Address:2920 DR ANDREW J BROWN AVE

Box:270

City:INDIANAPOLIS

State:IN

ZIP:46206-0270

Country:US

Info Phone Num:317-923-3211 Emergency Phone Num:317-923-3

233

CAGE:DO828

=== Contractor Identification ===

Company Name: BRULIN & COMPANY, INC.

Box:270-B

City: INDIANAPOLIS

State:IN

ZIP:46206-0270

Country:US

Phone:317-923-3211

CAGE:DO828

Company Name:BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE

Box:270

City: INDIANAPOLIS

State:IN

ZIP:46205-0270 Country:US

Phone:317-923-3211

CAGE:94058

====== Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1
======================================
Effects of Overexposure:BRIEF EXPOSURES: DIZZ,MILD SKIN & EYE IRRIT. (EXCESSIVE EXPOSURE)-HDCH,DRUM, (SEE SUPP DATA)
======================================
First Aid:EYES: FLUSH W/ WATER FOR 15 MIN. INHAL: REMOVE TO FRESH AIR. IF BREATH STOPS
GIVE ARTIFICIAL RESPIRATION. INGEST: INDUCE VOMIT. (ASPIRATION IS A HAZARD-GE MSDS-REF) CONSULT MD IF ANY SYMPTOMS PERSIST. (SKIN: WASH W/.WARM H*2O & SOAP,SEE MD-GE MSDS REF
======================================
Flash Point:NONE Lower Limits:7.5% Upper Limits:15% Extinguishing Media:WATER FOG. Fire Fighting Procedures:NIOSH/MSHA APPRVD PRESS DEMAND SCBA & FULL PROT EQUIP. Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE H CL AND PHOSGENE.
========= Accidental Release Measures ==========
Spill Release Procedures:SMALL SPILLS: ABSORB ON SOLID ABSORBENT. LARGE SPILL: USE PROPER BREATH EQUIPMENT AND ABSORB ON SOLID ABSORBENT ALLOW TO EVAPORATE. KEEP OUT OF WATER SUPPLY AND INHABITIED BUILDINGS.
=========== Handling and Storage ============

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS IN A COOL, VENTILATIED AREA. KEEP WATER-FREE.(GE-MSDS-REF

Fraction by Wt: 100%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

). DO NOT SMOKE WHEN
USING PRODUCT.
Other Proportions: PROVIDE MEDICAL MON

Other Precautions:PROVIDE MEDICAL MONITORING OF THOSE REGULARLY EXPOSED TO THIS PRODUCT IN THE WORKPLACE, PRECLUDE THOSE W/ CNS,LIVER,OR HEART DISEASE FROM EXPOSURE.(GE MSDS REF)

====== Exposure Controls/Personal Protection ========

Respiratory Protection:MFR RECMS NIOSH/MSHA APPRVD RESPIRATOR FOR CHLORINATED SOLVENTS.

Ventilation: MECHANICAL (GENERAL) SUFFICIENT TO KEEP BELOW TLV.

Protective Gloves: RECOMMENDED

Eye Protection: RECO

MMENDED

Other Protective Equipment: (AS REQUIRED TO PREVENT LIQUID CONTACT W/ SKIN-GE MSDS REF)

Supplemental Safety and Health

SPEC: TYPE I. OVEREXPOSURE: IMPAIRED JUDGEMENT, UNCOM, DERMAT, EYE IRRIT. GE MSDS REF) CONTAINER SIZE: 55 GAL DRUM

======== Physical/Chemical Properties ==========

HCC:T4

Boiling Pt:B.P. Text:165F,74C Melt/Freeze Pt:M.P/F.P Text: